

# PRODUCT DATASHEET LED VALUE STICK 7 W/6500 K E14 GEN4

LED VALUE STICK | LED lamps, classic stick shape



#### Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

#### **Product benefits**

- Low energy consumption
- Attractive lamp appearance

#### **Product features**

- LED alternative to conventional lamps
- Mercury-free lamps



# TECHNICAL DATA

#### Electrical data

Nominal wattage	7 W
Construction wattage	7.00 W
Nominal voltage	220240 V
Nominal current	70 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

#### Photometrical data

Luminous flux	750 lm
Luminous efficacy	107 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	200 °
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	114.00 mm
Diameter	40.00 mm
Maximum diameter	40 mm
Product weight	25.00 g

# Temperatures & operating conditions

# Lifespan

Number of switching cycles	100000

# Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

# Capabilities

Dimmable	No
Diminable	INU

#### Certificates & Standards

Energy efficiency class	A+ 1)
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

# Country-specific categorizations

Order reference	LVSTICK 7W/865
Energy labelling regulation data acc EU 2019/2015	

Light source cap-type (or other electric interface)	E14
Length	114.00 mm
Height	40.00 mm
Width	40.00 mm

#### DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED Value Stick 7W 6500K AC08531 AC08532

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075126701	Folding box 1	43 mm x 43 mm x 117 mm	53.00 g	0.21 dm <sup>3</sup>
4058075126718	Shipping box 10	218 mm x 92 mm x 132 mm	510.00 g	2.65 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854099953	Shipping box 10	218 mm x 92 mm x 132 mm	450.00 g	2.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.