

# PRODUCT DATASHEET LED PFM CLAS A 9 W/2700 K E27 FR DIM

LED PERFORMANCE CLASSIC A DIMMABLE | LED lamps, classic bulb shape, with retrofit screw base



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### Product benefits

- Very high dimmer compatibility, see also www.ledvance.com/dim
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- $\,-\,$  No UV and near-IR radiation in the light beam
- Good quality of light
- Reliable operation thanks to brand quality

#### **Product features**

- Long lifetime up to 25,000 h
- Color rendering index Ra: ≥ 80
- High color consistency: < 6 SDCM
- Luminous efficacy: up to 117 lm/W
- Mercury-free lamps



– Operating temperature from -20  $^{\circ}\text{C}$  to up to +40  $^{\circ}\text{C}$ , up to 95 % relative humidity

# TECHNICAL DATA

# Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	45 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.80

# Photometrical data

Luminous flux	806 lm
Luminous efficacy	89 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	240 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	108.00 mm
Diameter	61.50 mm
Maximum diameter	62 mm
Product weight	80.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

# Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

#### Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

# Capabilities

Dimmable	Yes

#### Certificates & Standards

Energy efficiency class	A+ <sup>1)</sup>
Energy consumption	9.00 kWh/1000h

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

# Country-specific categorizations

Order reference

Energy labelling regulation data acc EU 2019/2015		
Light source cap-type (or other electric interface)	E27	
Length	108.00 mm	
Height	61.50 mm	
Width	61.50 mm	

LPCLADIM 9W/827

#### DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LED PFM CLA 9W 2700K DIM

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075215313	Folding box	39 mm x 39 mm x 109 mm	59.00 g	0.17 dm <sup>3</sup>
4058075215320	Shipping box 10	332 mm x 138 mm x 147 mm	1124.00 g	6.73 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.