

PRODUCT DATASHEET LED PFM CLAS A 13 W/2700 K E27 FR DIM

LED PERFORMANCE CLASSIC A DIMMABLE | LED lamps, classic bulb shape, with retrofit screw base



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Very high dimmer compatibility, see also www.ledvance.com/dim
- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- $\,-\,$ No UV and near-IR radiation in the light beam
- Good quality of light
- Reliable operation thanks to brand quality

Product features

- Long lifetime up to 25,000 h
- Color rendering index Ra: ≥ 80
- High color consistency: < 6 SDCM
- Luminous efficacy: up to 117 lm/W
- Mercury-free lamps





– Operating temperature from -20 $^{\circ}\text{C}$ to up to +40 $^{\circ}\text{C}$, up to 95 % relative humidity

TECHNICAL DATA

Electrical data

Nominal wattage	13 W
Construction wattage	13.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	100 W
Nominal current	60 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.90

Photometrical data

Luminous flux	1521 lm
Nominal useful luminous flux 90°	1521 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	220 °
Warm-up time (60 %)	< 1.00 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	120.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	70.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	E 1)
Energy consumption	13.00 kWh/1000h
Photobiological safety group acc. to EN62778	RG1
Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (low Country-specific categorizations)	west efficiency)
	west efficiency) LPCLADIM 13W/82
Country-specific categorizations	
Country-specific categorizations Order reference	
Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015	LPCLADIM 13W/82
Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface)	LPCLADIM 13W/82 E27
Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Correlated colour temperature type	LPCLADIM 13W/82 E27 SINGLE_VALUE
Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Correlated colour temperature type Length	E27 SINGLE_VALUE 120.00 mm
Country-specific categorizations Order reference Energy labelling regulation data acc EU 2019/2015 Light source cap-type (or other electric interface) Correlated colour temperature type Length Height	E27 SINGLE_VALUE 120.00 mm 60.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075532403	Folding box 1	62 mm x 62 mm x 120 mm	87.00 g	0.46 dm ³
4058075532410	Shipping box 10	323 mm x 134 mm x 133 mm	1014.00 g	5.76 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.