

PRODUCT DATASHEET LED VALUE CLAS A 8 W/6500 K E27

LED VALUE CLASSIC A | LED lamps, classic bulb shape



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

Product features

- Color rendering index R_a : ≥ 80
- Not dimmable
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	220240 V
Nominal current	62 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz

Photometrical data

Luminous flux	806 lm
Luminous efficacy	100 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865

Dimensions & Weight

Overall length	105.00 mm
Diameter	59.00 mm
Product weight	20.00 g

Temperatures & operating conditions

Additional product data

Base (standard designation)	E27
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Certificates & Standards

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

Country-specific categorizations

Order reference	LVCLA60 8W/865	
Energy labelling regulation data acc EU 2019/2015		
Light source cap-type (or other electric interface)	E27	
Length	105.00 mm	
Height	59.00 mm	
Width	59.00 mm	
EPREL ID	1403225	

AC24710

LOGISTICAL DATA

Model number

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075383920	Folding box 3	182 mm x 62 mm x 117 mm	108.00 g	1.32 dm ³
4099854254802	Shipping box 24	506 mm x 192 mm x 130 mm	889.00 g	12.63 dm³
4058075383937	Shipping box 24	506 mm x 192 mm x 130 mm	1105.00 g	12.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.