

## PRODUCT DATASHEET

### LED VALUE CLASS A 75 10 W/2700 K E27

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Can be easily fitted instead of ordinary light bulbs

#### Product features

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering CRI  $\geq 80$  and color stability throughout the life of the lamp




TECHNICAL DATA

Electrical data

|  |             |
|--|-------------|
| Nominal wattage                        | 10 W        |
| Construction wattage                   | 10.00 W     |
| Nominal voltage                        | 220...240 V |
| Operating mode                         | AC Mains    |
| Claimed equiv. conventional lamp power | 75 W        |
| Nominal current                        | 70 mA       |
| Inrush current                         | 1.25 A      |
| Operating frequency                    | 50/60 Hz    |
| Mains frequency                        | 50/60 Hz    |
| Max. lamp number on MCB B10 A          | 219         |
| Max. lamp number on MCB B16 A          | 229         |
| Total harmonic distortion              | 111.70 %    |
| Power factor $\lambda$                 | 0.65        |

Photometrical data

|   |                           |
|---|---------------------------|
| Luminous flux                           | 1055 lm                   |
| Luminous efficacy                       | 105 lm/W                  |
| Lumen main.fact.at end of nom.life time | 0.93                      |
| Color temperature                       | 2700 K                    |
| Color rendering index Ra                | 80                        |
| Light color                             | 827                       |
| Standard deviation of color matching    | $\leq 6$ sdc <sub>m</sub> |
| Flickering metric (Pst LM)              | 1.0                       |
| Stroboscope effect metric (SVM)         | 0.4                       |




349927\_2700K\_Evl\_5630.eps

Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 150 °    |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

Dimensions & Weight



|                  |           |
|------------------|-----------|
| Overall length   | 109.00 mm |
| Diameter         | 60.00 mm  |
| Maximum diameter | 60 mm     |
| Product weight   | 26.00 g   |

Lifespan

|  |         |
|--|---------|
| Lifespan L70/B50 at 25 °C                    | 10000 h |
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.93    |

Additional product data

|                             |        |
|-----------------------------|--------|
| Base (standard designation) | E27    |
| Mercury content             | 0.0 mg |
| Mercury-free                | Yes    |

Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

|  |                 |
|--|-----------------|
| Energy efficiency class                      | F 1)            |
| Energy consumption                           | 10.00 kWh/1000h |
| Standards                                    | CE / UKCA / EAC |
| Photobiological safety group acc. to EN62778 | RG1             |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | VALUECLA75 10W/ |
|-----------------|-----------------|

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|  |  |
|--|--|
| Lighting technology used                             | LED                                    |
| Non-directional or directional                       | NDLS                                   |
| Mains or non-mains                                   | MLS                                    |
| Light source cap-type (or other electric interface)  | E27                                    |
| Connected light source (CLS)                         | No                                     |
| Color-tuneable light source                          | No                                     |
| Envelope   | No                                     |
| High luminance light source                          | No                                     |
| Anti-glare shield                                    | No                                     |
| Correlated colour temperature type                   | SINGLE_VALUE                           |
| Standby power  | 0 W                                    |
| Claim of equivalent power                            | Yes                                    |
| Length   | 109.00 mm                              |
| Height   | 60.00 mm                               |
| Width  | 60.00 mm                               |
| Chromaticity coordinate x                            | 0,458                                  |
| Chromaticity coordinate y                            | 0,410                                  |
| R9 Colour rendering index                            | 1                                      |
| Beam angle correspondence                            | SPHERE_360                             |
| Survival factor                                      | 0.9                                    |
| Displacement factor                                  | 0.965                                  |
| LED light source replaces a fluorescent light source | No                                     |
| EPREL ID   | 1403213,523312,1381368,1857051,1855177 |




Model number


AC31154,AC24697,AC44917,AC55986,AC56438,AC55986

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### DOWNLOAD DATA

| Documents and certificates   |                                 | Document name   |
|--|---------------------------------|---|
|  | Declarations of conformity      | EC Declaration of Conformity CLA Non Dim AC31141-56 AC31177-9 AC34531-3 |
|  | Declarations of conformity      | LED CLASSIC A_P NON-DIM   |
|  | Declarations of conformity UKCA | LED CLASSIC A_P NON-DIM   |

| Photometric and lighting design files  |                             | Document name             |
|--|-----------------------------|---------------------------|
|  | Spectral power distribution | 349927_2700K_Evl_5630.eps |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075479036 | Folding box<br>2             | 61 mm x 116 mm x 142 mm              | 67.00 g      | 1.00 dm <sup>3</sup> |
| 4058075479043 | Shipping box<br>20           | 316 mm x 242 mm x 126 mm             | 821.00 g     | 9.64 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.