

PRODUCT DATASHEET LED VALUE HW 75 36 W/6500 K E27

LED VALUE CLASSIC A HIGH WATTAGE | LED lamps with classic bulbs, high wattage



Areas of application

- Suitable for indoor applications.
- Warehouses
- Workshops
- Stadiums
- Car parks

Product benefits

- Energy savings of up to 50 % compared to conventional compact fluorescent lamps
- Accessory cover works as a reflector and increase the illuminance up to 100 %
- Wide beam angle: 200°
- Long lifetime of up to 20,000 h
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time

Product features

- Luminous efficacy: up to 100 lm/W
- Color rendering index Ra: ≥ 80
- Power factor: 0.9
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	36 W
Construction wattage	36.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	156 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.90

Photometrical data

Luminous flux	3600 lm
Nominal useful luminous flux 90°	3600 lm
Luminous efficacy	100 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	200 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	206.00 mm
Diameter	118.00 mm
Maximum diameter	118 mm

Product weight	182.00 g
Temperatures & operating conditions	
Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Capabilities	
Dimmable	No
Certificates & Standards	
Type of protection	IP20
Standards	CB / EMC / RoHS
Photobiological safety group acc. to EN62778	RG0
Country-specific categorizations	
Order reference	LV HW 36W/865 2
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E27
Length	206.00 mm
Height	118.00 mm

LOGISTICAL DATA

Width

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075723450	Folding box 1	125 mm x 125 mm x 220 mm	294.00 g	3.44 dm ³
4058075723467	Shipping box 10	642 mm x 264 mm x 245 mm	3797.00 g	41.52 dm ³

118.00 mm

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.