

# PRODUCT DATASHEET LED Star PAR16 80 36° 6.9W 827 GU10

LED STAR PAR16 | LED reflector lamps PAR16 with retrofit pin base



#### Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

## Product features

- LED alternative to conventional high voltage lamps
- Mercury-free lamps






## TECHNICAL DATA

## Electrical data

Nominal wattage	6.9 W
Construction wattage	6.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	80 W
Nominal current	50 mA
Type of current	AC
Inrush current	4.84 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	116
Max. lamp number on MCB B16 A	184
Total harmonic distortion	150 %
Power factor $\lambda$	> 0.50

## Photometrical data

Luminous intensity	860 cd
Luminous flux	575 lm
Nominal useful luminous flux 90°	575 lm
Luminous efficacy	83 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	860 cd
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



OS S10x18 2700K

# Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

## Dimensions & Weight

Overall length	54.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	39.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	97.5 °C

## Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

## Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	7.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1
ILCOS Order reference	DRPAR-6,9/827-220-240-GU10-50/36 LSPAR168036 6,9
OGISTICAL DATA	
OGISTICAL DATA  Temperature range at storage	-20+80 °C
Temperature range at storage	-20+80 °C
Temperature range at storage Energy labelling regulation data acc EU 2019/2015	-20+80 °C
Temperature range at storage Energy labelling regulation data acc EU 2019/2015	
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used	LED
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional	LED DLS
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains	LED DLS MLS
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)	LED DLS MLS GU10
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)	LED DLS MLS GU10 No
Temperature range at storage  Inergy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source	LED DLS MLS GU10 No
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope	LED DLS MLS GU10 No No
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source	LED DLS MLS GU10 No No No No
Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield	LED DLS MLS GU10 No No No No No
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)	LED DLS MLS GU10
Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield  Correlated colour temperature type	LED DLS MLS GU10 No No No No No SINGLE_VALUE

54.00 mm

Length

Height	50.00 mm
Width	50.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.90
Displacement factor	0.70
LED light source replaces a fluorescent light source	No
EPREL ID	1403122,522991,734488,1368237,1841988
Model number	AC32742,AC35478,AC45665,AC26240,AC57960

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED SPOT PAR16	
PDF	Declarations of conformity	LED PA16	
PDF	Declarations of conformity UKCA	LED PAR16	
	Photometric and lighting design files	Document name	
	IES file (IES)	PAR16 M3 80 36 2700K GU10	
	LDT file (Eulumdat)	PAR16 M3 80 36 2700K GU10	
	Light distribution curve type polar	PAR16 M3 80 36 2700K GU10	
	Spectral power distribution	OS S10x18 2700K	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075112605	Folding box	52 mm x 52 mm x 95 mm	49.00 g	0.26 dm <sup>3</sup>
4058075617629	Shipping box	185 mm x 120 mm x 76 mm	360.00 g	1.69 dm³
4058075112612	Shipping box 10	257 mm x 110 mm x 70 mm	518.00 g	1.98 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.