

PRODUCT DATASHEET LED Star MR16 35 120° 4.3W 827 GU5.3

LED STAR MR16 12 V | Low-voltage LED reflector lamps MR16 with retrofit pin base



Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Product features

- LED alternative to low voltage halogen lamps
- Mercury-free lamps






TECHNICAL DATA

Electrical data

Nominal wattage	4.3 W
Construction wattage	4.30 W
Nominal voltage	12 V
Operating mode	12V AC/DC
Claimed equiv. conventional lamp power	35 W
Nominal current	540 mA
Type of current	AC/DC
Inrush current	12.8 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	28
Max. lamp number on MCB B16 A	36
Total harmonic distortion	< 120 %
Power factor λ	> 0.50

Photometrical data

Luminous intensity 125 cd Luminous flux 396 lm Luminous efficacy 92 lm/W Lumen main.fact.at end of nom.life time 0.95 Light color (designation) Warm White Color temperature 2700 K Color rendering index Ra 80 Light color 827 Standard deviation of color matching ≤6 sdcm Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1 Stroboscope effect metric (SVM) 0.4		
Luminous efficacy 92 lm/W Lumen main.fact.at end of nom.life time 0.95 Light color (designation) Warm White Color temperature 2700 K Color rendering index Ra 80 Light color 827 Standard deviation of color matching ≤6 sdcm Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1	Luminous intensity	125 cd
Lumen main.fact.at end of nom.life time 0.95 Light color (designation) Warm White Color temperature 2700 K Color rendering index Ra 80 Light color 827 Standard deviation of color matching ≤6 sdcm Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1	Luminous flux	396 lm
Light color (designation)Warm WhiteColor temperature2700 KColor rendering index Ra80Light color827Standard deviation of color matching≤6 sdcmRated peak intensity125 cdRated LLMF at 6,000 h0.80Flickering metric (Pst LM)1	Luminous efficacy	92 lm/W
Color temperature2700 KColor rendering index Ra80Light color827Standard deviation of color matching≤6 sdcmRated peak intensity125 cdRated LLMF at 6,000 h0.80Flickering metric (Pst LM)1	Lumen main.fact.at end of nom.life time	0.95
Color rendering index Ra 80 Light color 827 Standard deviation of color matching ≤6 sdcm Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1	Light color (designation)	Warm White
Light color 827 Standard deviation of color matching ≤6 sdcm Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1	Color temperature	2700 K
Standard deviation of color matching ≤6 sdcm Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1	Color rendering index Ra	80
Rated peak intensity 125 cd Rated LLMF at 6,000 h 0.80 Flickering metric (Pst LM) 1	Light color	827
Rated LLMF at 6,000 h Clickering metric (Pst LM) 1	Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM) 1	Rated peak intensity	125 cd
	Rated LLMF at 6,000 h	0.80
Stroboscope effect metric (SVM) 0.4	Flickering metric (Pst LM)	1
	Stroboscope effect metric (SVM)	0.4



LED MR16 35 GU5.3

Light technical data

Beam angle	120 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	44.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	28.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	86 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.95
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	GU5.3
Mercury content	0.0 mg

Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	5.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LSMR1635120 4,3
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20+80 °C
------------------------------	-----------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GU5.3
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	Yes
Length	44.00 mm

Height	50.00 mm
Width	50.00 mm
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	1441726
Model number	AC49230

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	LED MR 16 50 120 CL GU5.3

Photometric and lighting design files Document name	
IES file (IES)	MR16 M3 35 120 827 GU5.3
LDT file (Eulumdat)	MR16 M3 35 120 827 GU5.3
Light distribution curve type polar	MR16 M3 35 120 827 GU5.3
Spectral power distribution	LED MR16 35 GU5.3

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854098970	Folding box 2	51 mm x 102 mm x 95 mm	71.00 g	0.49 dm ³
4099854098987	Shipping box 6	174 mm x 115 mm x 74 mm	307.00 g	1.48 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee
- Further information see www.ledvance.com/low-voltage-ledlamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.