

# PRODUCT DATASHEET LED Superstar R50 60 36° DIM 5.9W 927 E14

LED SUPERSTAR R50 | Dimmable LED reflector lamps R50 with retrofit screw base



#### Areas of application

- Display cabinets and shop windows
- Museums, art galleries
- Exhibition rooms
- Hospitality
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Very long lifetime of up to 25,000 h
- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of halogen lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### Product features

- Professional LED alternative to halogen lamps
- Good color rendering: up to R<sub>a</sub> 90
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps





## TECHNICAL DATA

## Electrical data

Nominal wattage	5.9 W
Construction wattage	5.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	60 W
Nominal current	32 mA
Type of current	AC
Inrush current	0.9 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	162
Max. lamp number on MCB B16 A	259
Total harmonic distortion	120 %
Power factor $\lambda$	0.70

## Photometrical data

Luminous intensity	607 cd
Luminous flux	350 lm
Nominal useful luminous flux 90°	350 lm
Luminous efficacy	59 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	90
Light color	927
Standard deviation of color matching	≤5 sdcm
Rated peak intensity	607 cd
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



Everlight 67-23ST HKE 2700K

# Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

## Dimensions & Weight

Overall length	85.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	49.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	99 °C

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.96

# Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes

All technical parameters apply to the entire lamp / D production process for light-emitting diodes, the typ Product remark for the technical LED parameters are purely statistic not necessarily match the actual technical parameter individual product, which can vary from the typical v	oical values shown al values that do ers of each
---	--

## Capabilities

<sup>1)</sup> Check dimmer compatibility at ledvance.com/compatibility

#### Certificates & Standards

Energy efficiency class	G <sup>1)</sup>
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

## Country-specific categorizations

Order reference	LEDSR5060D 5,9W
-----------------	-----------------

#### LOGISTICAL DATA

Temperature range at storage	-20+80 °C

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	Yes
Length	85.00 mm

Height	50.00 mm
Width	50.00 mm
Chromaticity coordinate x	0.4531
Chromaticity coordinate y	0.4010
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.9
Displacement factor	0.7
LED light source replaces a fluorescent light source	No
EPREL ID	1403192,522929,1368258,1842013,2499552
Model number	AC32660,AC45733,AC24572,AC57976,AC57976,AC91835

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED SPOT R50 PAR16	
PDF	Declarations of conformity	LED R39 R50 PAR16	
PDF	Declarations of conformity UKCA	LED R39 R50 PA16	
	Photometric and lighting design files	Document name	
	Spectral power distribution	Everlight 67-23ST HKE 2700K	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075125940	Folding box 1	51 mm x 51 mm x 130 mm	64.00 g	0.34 dm <sup>3</sup>
4058075616400	Shipping box	174 mm x 115 mm x 106 mm	482.00 g	2.12 dm <sup>3</sup>

E14

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075125957	Shipping box 10	276 mm x 115 mm x 106 mm	875.00 g	3.36 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

E14