

PRODUCT DATASHEET

SST R63 60 36 ° 5.9 W/2700 K E27

LED SUPERSTAR R63 | Dimmable LED reflector lamps R63 with retrofit screw base



Areas of application

- Display cabinets and shop windows
- Museums, art galleries
- Hospitality
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Very long lifetime of up to 25,000 h
- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of halogen lamps thanks to compact design
- Instant 100 % light, no warm-up time

Product features

- Professional LED alternative to halogen lamps
- Good color rendering: up to R_a 90
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	5.9 W
Construction wattage	5.90 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	32 mA
Type of current	AC
Inrush current	1 A
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Max. lamp number on MCB B10 A	183
Max. lamp number on MCB B16 A	293
Power factor λ	> 0.50

Photometrical data

Luminous intensity	600 cd
Luminous flux	345 lm
Nominal useful luminous flux 90°	345 lm
Luminous efficacy	58 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥90
Light color	927
Standard deviation of color matching	≤5 sdcn
Rated peak intensity	600 cd
Rated LLMF at 6,000 h	0.80




Everlight 67-23ST HKE 2700K

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	102.00 mm
Diameter	63.00 mm
Maximum diameter	63 mm
Product weight	107.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	83 °C

Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
----------------	--

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	A+ ¹⁾
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	LEDSR6360D 5,9W
-----------------	-----------------



Energy labelling regulation data acc EU 2019/2015






Light source cap-type (or other electric interface)	E27
Length	102.00 mm
Height	63.00 mm
Width	63.00 mm
EPREL ID	1402946

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	R63 R80 E27
	Declarations of conformity	LED spot lamp R63 R80

Documents and certificates		Document name
	Declarations of conformity UKCA	LED spot lamp R63 R80
Photometric and lighting design files		Document name
	IES file (IES)	LEDPR6360D 5.9W 927 260V GL E27
	LDT file (Eulumdat)	LEDPR6360D 5.9W 927 260V GL E27
	Light distribution curve type polar	LEDPR6360D 5.9W 927 260V GL E27
	Spectral power distribution	Everlight 67-23ST HKE 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075097087	Blister 1	65 mm x 140 mm x 120 mm	122.00 g	1.09 dm ³
4058075097094	Shipping box 6	410 mm x 154 mm x 134 mm	900.00 g	8.46 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.