

PRODUCT DATASHEET LED Star Classic P 25 Filament 2.5W 840 Clear E14

LED Retrofit CLASSIC P | LED lamps, classic mini-ball shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Lamps with innovative LED "filament" technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

Product features





- Professional LED lamps for line voltage
- Not dimmable
- Beam angle: up to 300°
- Lifetime up to 15,000 h
- Lamp made of glass
- Good quality of light; color rendering index $R_{a}\!\!: \, \geq 80;$ constant chromaticity


TECHNICAL DATA

Electrical data


Nominal wattage	2.5 W
Construction wattage	2.50 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	25 W
Nominal current	19 mA
Type of current	AC
Inrush current	1.8 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	250
Max. lamp number on MCB B16 A	400
Power factor λ	> 0.50

Photometrical data

Luminous flux	250 lm
Nominal useful luminous flux 90°	250 lm
Luminous efficacy	100 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	≤0.4







A60230V75W9404MDV1E27AC3398301

Light technical data

Beam angle	300 °	
Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

Dimensions & Weight

Overall length	77.00 mm
Diameter	45,0 mm
Maximum diameter	45 mm
Product weight	15.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at to test point	60 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Continue of Chandrade	
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	3.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG0
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to country-specific categorizations	G (lowest efficiency)
	G (lowest efficiency) LEDSCLP25 2,5W/
Country-specific categorizations Order reference	
Country-specific categorizations Order reference	
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage	LEDSCLP25 2,5W/
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage	LEDSCLP25 2,5W/
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	LEDSCLP25 2,5W/ -20+80 °C
Country-specific categorizations Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	LEDSCLP25 2,5W/ -20+80 °C
Country-specific categorizations Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	LEDSCLP25 2,5W/ -20+80 °C LED NDLS
Country-specific categorizations Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	LEDSCLP25 2,5W/ -20+80 °C LED NDLS MLS
Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	LEDSCLP25 2,5W/ -20+80 °C LED NDLS MLS E14
Country-specific categorizations Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	LEDSCLP25 2,5W/ -20+80 °C LED NDLS MLS E14 No

Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Networked standby power for CLS	0 W
Claim of equivalent power	Yes
Length	77.00 mm
Height	45,0 mm
Width	45,0 mm
Chromaticity coordinate x	0.380
Chromaticity coordinate y	0.380
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.40
LED light source replaces a fluorescent light source	No
EPREL ID	1402973,523054
Model number	AC32444,AC17496

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name		
PDF	Declarations of conformity	LED lamps CLA,B,G,P		
	Photometric and lighting design files	Document name		
	Spectral power distribution	LISO spectral power distribution 4000K CRI80 v1		
	Spectral power distribution	A60230V75W9404MDV1E27AC3398301		
·				

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075434103	Folding box 1	46 mm x 49 mm x 130 mm	27.00 g	0.29 dm ³
4058075604896	Shipping box 6	159 mm x 111 mm x 106 mm	252.00 g	1.87 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.