

# PRODUCT DATASHEET SST CLAS P 40 4.5 W/2700 K E27

LED Retrofit CLASSIC P DIM | Dimmable LED lamps, classic mini-ball shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lamps with innovative LED "filament" technology
- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Design, dimensions, luminous flux comparable to an incandescent lamp

#### **Product features**

- LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Beam angle: up to 300°
- Lifetime up to 15,000 h
- Lamp made of glass



– Good quality of light; color rendering index  $R_{a:} \ge 80$ ; constant chromaticity

## TECHNICAL DATA

## Electrical data

| Nominal wattage                        | 4.5 W    |
|--|----------|
| Construction wattage                   | 4.50 W   |
| Nominal voltage                        | 220240 V |
| Claimed equiv. conventional lamp power | 40 W     |
| Nominal current                        | 22 mA    |
| Type of current                        | AC       |
| Inrush current                         | 2.8 A    |
| Operating frequency                    | 5060 Hz  |
| Mains frequency                        | 5060 Hz  |
| Max. lamp number on MCB B10 A          | 460      |
| Max. lamp number on MCB B16 A          | 736      |
| Power factor λ                         | > 0.70   |

## Photometrical data

| Luminous flux                           | 470 lm     |
|---|------------|
| Nominal useful luminous flux 90°        | 470 lm     |
| Luminous efficacy                       | 104 lm/W   |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Color temperature                       | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Light color                             | 827        |
| Standard deviation of color matching    | ≤6 sdcm    |
| Rated LLMF at 6,000 h                   | 0.80       |

# Light technical data

| Beam angle          | 320 °    |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

# Dimensions & Weight

| Overall length   | 77.00 mm |
|------------------|----------|
| Diameter         | 45.00 mm |
| Maximum diameter | 45 mm    |

| Product weight  | 18.00 g   |
|---|---|
| emperatures & operating conditions  |   |
| Ambient temperature range   | -20+40 °C   |
| Maximum temperature at tc test point  | 50 °C   |
| ifespan   |   |
| Number of switching cycles  | 100000  |
| Lumen maintenance at end of service lifetime                                | 0.70  |
| Rated lamp survival factor at 6,000 h                                       | ≥ 0.90  |
| Additional product data   |   |
| Base (standard designation)   | E27   |
| Mercury content   | 0.0 mg  |
| Mercury-free  | Yes   |
| Design / version  | Clear   |
| Product remark  | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / In preparation |
| Capabilities  |   |
| Dimmable  | Yes   |
| Certificates & Standards  |   |
| Energy efficiency class   | A++ 1)  |
| Energy consumption  | 5.00 kWh/1000h  |
| Type of protection  | IP20  |
| Standards   | CE  |
| Photobiological safety group acc. to EN62778                                | RG0   |
| ) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to B | Ξ (lowest efficiency)   |
|   | LEDOOLDAGD A FIM  |
| Order reference   | LEDSCLP40D 4,5W   |
| Energy labelling regulation data acc EU 2019/2015                           |   |
| Light source cap-type (or other electric interface)                         | E27   |

| Length | 77.00 mm |
|--------|----------|
| Height | 45.00 mm |
| Width  | 45.00 mm |

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075211063 | Folding box<br>1             | 46 mm x 46 mm x 93 mm                | 28.00 g      | 0.20 dm <sup>3</sup> |
| 4058075211070 | Shipping box<br>10           | 245 mm x 102 mm x 101 mm             | 353.00 g     | 2.52 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.