

PRODUCT DATASHEET LEDISON CLAS ST 40 CL 4 W/2700 K E27

LED Retrofit CLASSIC ST | LED lamps, classic Edison bulb shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

Product features

- LED lamps for line voltage
- Not dimmable
- Lifetime up to 15,000 h
- Beam angle: up to 360°
- Lamp made of glass
- Good quality of light; color rendering index $R_{a:} \ge 80$; constant chromaticity





TECHNICAL DATA

Electrical data

| Nominal wattage | 4 W |
|--|----------|
| Construction wattage | 4.00 W |
| Nominal voltage | 220240 V |
| Claimed equiv. conventional lamp power | 40 W |
| Nominal current | 32 mA |
| Type of current | AC |
| Inrush current | 3.7 A |
| Operating frequency | 5060 Hz |
| Mains frequency | 5060 Hz |
| Max. lamp number on MCB B10 A | 100 |
| Max. lamp number on MCB B16 A | 150 |
| Power factor λ | > 0.40 |

Photometrical data

| Luminous flux | 470 lm |
|---|------------|
| Nominal useful luminous flux 90° | 470 lm |
| Luminous efficacy | 117 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |
| Rated LLMF at 6,000 h | 0.80 |

Light technical data

| Beam angle | 300 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight

| Overall length | 143.00 mm |
|------------------|-----------|
| Diameter | 64.00 mm |
| Maximum diameter | 64 mm |

| Product weight | 46.00 g |
|--|--|
| Temperatures & operating conditions | |
| Ambient temperature range | -20+40 °C |
| Maximum temperature at tc test point | 50 °C |
| Lifespan | |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |
| Additional product data | |
| Base (standard designation) | E27 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
| Capabilities | |
| Dimmable | No |
| Certificates & Standards | |
| Energy efficiency class | E 1) |
| Energy consumption | 4.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE |
| Photobiological safety group acc. to EN62778 | RG1 |
| 1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E | (lowest efficiency) |
| Country-specific categorizations | |
| ILCOS | DRAS/C-4/827-220-240-E27-64 |
| Order reference | LEDISON40 4W/82 |
| Energy labelling regulation data acc EU 2019/2015 | |
| Light source cap-type (or other electric interface) | E27 |

| Correlated colour temperature type | SINGLE_VALUE |
|------------------------------------|--------------|
| Length | 143.00 mm |
| Height | 64.00 mm |
| Width | 64.00 mm |
| EPREL ID | 1403388 |
| Model number | AC24314 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4052899972346 | Blister 1 | 67 mm x 140 mm x 185 mm | 74.00 g | 1.74 dm ³ |
| 4052899420861 | Shipping box 6 | 416 mm x 153 mm x 201 mm | 608.00 g | 12.79 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.