

# PRODUCT DATASHEET SPC.T26 2.3 W/2700 K E14

LED SPECIAL T26 | Small special LED lamps with E14 screw base



#### Areas of application

- Domestic refrigerators
- Atmospheric accent lighting throughout the home
- Small designer luminaires
- Sewing machines
- Outdoor use in suitable outdoor luminaires only

## **Product benefits**

- Extremely small dimensions
- Good all-around light emission
- Ideal for decorative and free-burning applications
- Long lifetime of up to 15,000 h
- Three year guarantee
- Lower energy consumption than incandescent or halogen lamps

## Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index  $R_a$ :  $\geq$  80; constant chromaticity





# TECHNICAL DATA

# Electrical data

Nominal wattage	2.3 W
Construction wattage	2.30 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	20 W
Nominal current	24 mA
Type of current	AC
Operating frequency	50 Hz
Mains frequency	50 Hz
Power factor $\lambda$	> 0.40

# Photometrical data

Luminous flux	200 lm
Nominal useful luminous flux 90°	200 lm
Luminous efficacy	86 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	160 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	63.00 mm
Diameter	25.00 mm
Maximum diameter	25 mm
Product weight	15.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C	
Lifespan		
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Rated lamp survival factor at 6,000 h	≥ 0.90	
Additional product data		
Base (standard designation)	E14	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy efficiency class	F 1)	
Energy consumption	3.00 kWh/1000h	
Type of protection	IP20	
Photobiological safety group acc. to EN62778	RG1	
Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E Country-specific categorizations	E (lowest efficiency)	
Order reference	LEDVT26 2,3W/82	
Energy labelling regulation data acc EU 2019/2015		
Light source cap-type (or other electric interface)	E14	
Correlated colour temperature type	SINGLE_VALUE	
Length	63.00 mm	
	25.00 mm	
Height	25.00 mm	
Height Width	25.00 mm 25.00 mm	

#### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### **DOWNLOAD DATA**

Photometric and lighting design files	Document name
IES file (IES)	LEDVT26 2,3W/827 230V FR E14 OSRAM

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075509566	Folding box 1	51 mm x 51 mm x 99 mm	26.00 g	0.26 dm <sup>3</sup>
4058075509573	Shipping box 10	266 mm x 109 mm x 112 mm	372.00 g	3.25 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.