

PRODUCT DATASHEET

LED PIN 20 300° 1.9W 827 Clear G9

LED PIN G9 | LED lamps with retrofit pin base G9



Areas of application

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Good all-around light emission
- Long lifetime of up to 15,000 h
- Ideal for decorative and free-burning applications
- Three year guarantee
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index $R_a \geq 80$; constant chromaticity



TECHNICAL DATA**Electrical data**

| | |
|--|-------------|
| Nominal wattage | 1.9 W |
| Construction wattage | 1.90 W |
| Nominal voltage | 220...240 V |
| Operating mode | AC Mains |
| Claimed equiv. conventional lamp power | 20 W |
| Nominal current | 17 mA |
| Type of current | AC |
| Inrush current | 4.72 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 127 |
| Max. lamp number on MCB B16 A | 159 |
| Total harmonic distortion | 143 % |
| Power factor λ | > 0.40 |

Photometrical data

| | |
|---|---------------------|
| Luminous flux | 200 lm |
| Luminous efficacy | 105 lm/W |
| Lumen main.fact.at end of nom.life time | 0.93 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdc _m |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.4 |



349927_2700K_Evl_5630.eps

Light technical data

| | |
|---------------------|----------|
| Beam angle | 300 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| | |
|------------------|----------|
| Overall length | 43.00 mm |
| Diameter | 14.00 mm |
| Maximum diameter | 14 mm |
| Product weight | 5.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Maximum temperature at tc test point | 89.5 °C |

Lifespan

| | |
|--|---------|
| Lifespan L70/B50 at 25 °C | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.93 |

Additional product data

| | |
|-----------------------------|--|
| Base (standard designation) | G9 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|--|-----------------|
| Energy efficiency class | F 1) |
| Energy consumption | 2.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG1 |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LEDPIN20 CL 1,9 |
|-----------------|-----------------|

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015







| | |
|---|--------------|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Light source cap-type (or other electric interface) | G9 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |

| | |
|--|--------------------------------|
| Standby power | 0 W |
| Claim of equivalent power | Yes |
| Length | 43.00 mm |
| Height | 14.00 mm |
| Width | 14.00 mm |
| Chromaticity coordinate x | 0.4578 |
| Chromaticity coordinate y | 0.4101 |
| R9 Colour rendering index | 1 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.9 |
| Displacement factor | >0.5 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 1403251,522874,1856551,2365053 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|---|---------------------------------|---------------------------|
|  | Declarations of conformity | LED PIN 40 NON DIM G9 |
|  | Declarations of conformity | LED PIN G9 |
|  | Declarations of conformity | LED lamps |
|  | Declarations of conformity UKCA | LED PIN G9 |
|  | Declarations of conformity UKCA | LED lamps |
| Photometric and lighting design files | | Document name |
|  | Spectral power distribution | 349927_2700K_Evl_5630.eps |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075449831 | Folding box 2 | 20 mm x 49 mm x 95 mm | 17.00 g | 0.09 dm ³ |
| 4058075432307 | Folding box 1 | 20 mm x 49 mm x 95 mm | 12.00 g | 0.09 dm ³ |
| 4058075626317 | Shipping box 6 | 109 mm x 79 mm x 104 mm | 76.00 g | 0.90 dm ³ |
| 4058075626416 | Shipping box 12 | 109 mm x 79 mm x 104 mm | 120.00 g | 0.90 dm ³ |
| 4058075432314 | Shipping box 10 | 119 mm x 109 mm x 104 mm | 151.00 g | 1.35 dm ³ |
| 4058075449855 | Shipping box 160 | | | |
| 4058075626324 | Shipping box 48 | 236 mm x 176 mm x 237 mm | 1154.00 g | 9.84 dm ³ |
| 4058075626423 | Shipping box 96 | 236 mm x 176 mm x 237 mm | 1394.00 g | 9.84 dm ³ |
| 4058075432321 | Shipping box 80 | | | |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.