

PRODUCT DATASHEET LED PIN 20 320° DIM 2W 827 Clear G4

LED PIN 12 V DIM | Dimmable low-voltage 12 V LED lamps with retrofit pin base



Areas of application

- Decorative applications
- Atmospheric accent lighting throughout the home
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Variable use at Direct Current and Alternating Current
- Good all-around light emission
- Ideal for decorative and free-burning applications
- Very long lifetime of up to 25,000 h
- Four year guarantee
- Lower energy consumption than incandescent or halogen lamps

Product features

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Compatible with many common conventional and electronic control gears (see also compatibility list)
- LED alternative to low voltage halogen lamps
- Base: G4, GY6.35





TECHNICAL DATA

Electrical data

| Nominal wattage | 2 W |
|--|-------------------------|
| Construction wattage | 2.00 W |
| Nominal voltage | 12 V |
| Operating mode | 12V AC/DC ¹⁾ |
| Claimed equiv. conventional lamp power | 20 W |
| Nominal current | 170 mA |
| Type of current | AC/DC |
| Inrush current | 2.38 A |
| Max. lamp number on MCB B10 A | 35 |
| Max. lamp number on MCB B16 A | 52 |
| Total harmonic distortion | 37 % |
| Power factor λ | > 0.90 |

¹⁾ Check ECG compatibility at ledvance.com/compatibility

Photometrical data

| Luminous flux | 200 lm |
|---|------------|
| Luminous efficacy | 100 lm/W |
| Lumen main.fact.at end of nom.life time | 0.96 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcm |
| Flickering metric (Pst LM) | 1.0 |
| Stroboscope effect metric (SVM) | 0.4 |



349927_2700K_Evl_5630.eps

Light technical data

| Beam angle | 320 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| Overall length | 38.00 mm |
|------------------|----------|
| Diameter | 14.00 mm |
| Maximum diameter | 14 mm |
| Product weight | 5.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|--------------------------------------|-----------|
| Maximum temperature at tc test point | 78.6 °C |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h |
|--|---------|
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.96 |

Additional product data

| Base (standard designation) | G4 |
|-----------------------------|--|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| Dimmable | Yes 1) |
|----------|--------|
| | 1.00 |

¹⁾ Check dimmer compatibility at ledvance.com/compatibility

Certificates & Standards

| Energy efficiency class | F 1) |
|--|-----------------|
| Energy consumption | 2.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG1 |

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Temperature range at storage

| Order reference | LEDPIN20D CL 2W |
|-----------------|-----------------|
| LOGISTICAL DATA | |

-20...+80 °C

Energy labelling regulation data acc EU 2019/2015

| Lighting technology used | LED |
|---|------|
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | G4 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |

| Correlated colour temperature type | SINGLE_VALUE |
|--|---|
| Standby power | 0 W |
| Claim of equivalent power | Yes |
| Length | 38.00 mm |
| Height | 14.00 mm |
| Width | 14.00 mm |
| Chromaticity coordinate x | 0.4578 |
| Chromaticity coordinate y | 0.4101 |
| R9 Colour rendering index | 1 |
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.9 |
| Displacement factor | >0.9 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 1402999,522864,1856538,2365047 |
| Model number | AC32099,AC17652,AC58929,AC58929,AC84134 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

| | Documents and certificates | ificates Document name | |
|-----|---------------------------------|------------------------|--|
| PDF | Declarations of conformity | LED PIN 20 NON-DIM 12V | |
| PDF | Declarations of conformity | LED PIN G4 GY6.35 | |
| PDF | Declarations of conformity | LED lamp | |
| PDF | Declarations of conformity UKCA | LED PIN G4 GY6.35 | |
| PDF | Declarations of conformity UKCA | LED lamp | |

| Photometric and lighting design files | Document name | |
|---------------------------------------|---------------------------|--|
| Spectral power distribution | 349927_2700K_EvI_5630.eps | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075431904 | Folding box 1 | 20 mm x 49 mm x 95 mm | 12.00 g | 0.09 dm ³ |
| 4058075431911 | Shipping box 10 | 119 mm x 109 mm x 104 mm | 160.00 g | 1.35 dm ³ |
| 4058075622630 | Shipping box 6 | 109 mm x 79 mm x 104 mm | 103.00 g | 0.90 dm ³ |
| 4058075431928 | Shipping box 80 | 256 mm x 236 mm x 237 mm | 1668.00 g | 14.32 dm ³ |
| 4058075622647 | Shipping box 48 | 236 mm x 176 mm x 237 mm | 1154.00 g | 9.84 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.