

PRODUCT DATASHEET

ST8A-EM 8.7 W/6500 K 600 mm

SubstiTUBE Advanced | LED tubes for electromagnetic control gears



Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores
- Industry

Product benefits

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- Energy savings of up to 60 % (compared to T8 fluorescent lamp on CCG)
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Also suitable for operation at low temperatures

Product features

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Bright, robust and durable
- Uniform illumination
- Tube made of glass
- Mercury-free and RoHS compliant



- Type of protection: IP20
- Integrated ECG with high power factor

TECHNICAL DATA

Electrical data

| | |
|------------------------|-------------|
| Nominal wattage | 8.7 W |
| Construction wattage | 8.70 W |
| Nominal voltage | 220...240 V |
| Nominal current | 40 mA |
| Type of current | AC |
| Operating frequency | 50...60 Hz |
| Mains frequency | 50...60 Hz |
| Power factor λ | > 0.90 |

Photometrical data

| | |
|---|---------------------|
| Luminous flux | 1050 lm |
| Luminous efficacy | 120 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Daylight |
| Color temperature | 6500 K |
| Color rendering index Ra | ≥80 |
| Light color | 865 |
| Standard deviation of color matching | ≤6 sdc _m |

Light technical data

| | |
|---------------|------------|
| Beam angle | ˆ 160.00 ° |
| Starting time | < 1.0 s |

Dimensions & Weight

| | |
|----------------|-----------|
| Overall length | 604.00 mm |
| Diameter | 28.00 mm |
| Product weight | 120.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+45 °C |
| Maximum temperature at tc test point | 75 °C |

Lifespan

| | |
|----------------------------|-------|
| Number of switching cycles | 50000 |
|----------------------------|-------|

| | |
|--|------|
| Lumen maintenance at end of service lifetime | 0.70 |
|--|------|

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | G13 |
| Mercury content | 0.0 mg |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|--------------------|------|
| Type of protection | IP20 |
| Standards | CB |

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | ST8A-0.6M 8,7W/ |
|-----------------|-----------------|

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|---|-----------|
| Light source cap-type (or other electric interface) | G13 |
| Length | 604.00 mm |
| Height | 28.00 mm |
| Width | 28.00 mm |

Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075421509 | Sleeve 1 | 655 mm x 28 mm x 28 mm | 139.00 g | 0.52 dm ³ |
| 4058075421516 | Shipping box 25 | 710 mm x 167 mm x 185 mm | 4062.00 g | 21.94 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/substitute
-

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.
-

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.