

PRODUCT DATASHEET

ST8V-UN 19 W/4000 K 1500 mm

SubstiTUBE T8 UNIVERSAL VALUE | LED tubes for electronic control gears (ECG), electromagnetic control gears (CCG) and mains



Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Corridors, stairways, parking garages
- Warehouses

Product benefits

- No bending thanks to glass technology
- Also suitable for operation at low temperatures
- Easy installation

Product features

- T8 LED tube made of glass with G13 base
- Compatible with conventional and many common electronic control gears (see also compatibility list) and line voltage
- Low flicker according to EU 2019/2020
- Uniform illumination
- Lifetime up to 30,000 h
- Mercury-free lamps



TECHNICAL DATA**Electrical data**

Nominal wattage	19 W
Construction wattage	19.00 W
Nominal voltage	220...240 V
Operating mode	Electronic control gear (ECG), Conventional control gear (CCG), Line voltage
Nominal current	90 mA ¹⁾
Type of current	AC
Inrush current	37 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz ²⁾
Max. lamp number on MCB B10 A	43
Max. lamp number on MCB B10 A - CCG without compensation	43
Max. lamp number on MCB B10 A - CCG with compensation	37
Max. lamp number on MCB B16 A	69
Max. lamp number on MCB B16 A - CCG without compensation	69
Max. lamp number on MCB B16 A - CCG with compensation	62
Power factor λ	> 0.90

1) 475 mA for ECG (HF)

2) 20-75KHz for ECG (HF)

Photometrical data

Luminous flux	2000 lm
Luminous efficacy	105 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcn
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	160 °
------------	-------

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	1500.00 mm
Length with base excl. base pins/connection	1498 mm
Diameter	28.00 mm
Tube diameter	26,7 mm
Base diameter	28,0 mm
Maximum diameter	28 mm
Product weight	284.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	62 °C

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	19.00 kWh/1000h
Type of protection	IP20
Standards	CE

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	ST8V-1.5M 19W/8
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------



Energy labelling regulation data acc EU 2019/2015




Light source cap-type (or other electric interface)	G13
Length	1500.00 mm
Height	28.00 mm
Width	28.00 mm
EPREL ID	1582633
Model number	AC11163

Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- For operation of LED TUBE T8 UN with a conventional control gear, the existing starter must be exchanged with the including LED starter in the LED tube packaging.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	Installation instructions for SubstiTube
	Extended installation guide	SubstiTUBE® T8 T5

Photometric and lighting design files		Document name
	IES file (IES)	ST8V 1,5M 19W 840 UN
	LDT file (Eulumdat)	ST8V 1,5M 19W 840 UN
	Light distribution curve type polar	ST8V 1,5M 19W 840 UN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075137547	Sleeve 1	1,605 mm x 29 mm x 29 mm	318.00 g	1.35 dm ³
4058075137554	Shipping box 10	1,652 mm x 210 mm x 115 mm	4020.00 g	39.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For current information see www.ledvance.com/substitute

Legal advice

– When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.