

PRODUCT DATASHEET HALOPAR 30 75 W 230 V 30° E27

HALOPAR® 30 | Halogen lamps with parabolic reflector PAR30, with screw base



Areas of application

- General illumination
- Workplace lighting
- Kitchen lighting
- Object lighting
- Accent lighting
- Shops
- Restaurants, hotels and similar prestigious applications

Product benefits

- Brilliant accent light
- With whole glass reflector for brilliant lighting effects
- Instant 100 % light, no warm-up time
- Approved for use in open luminaires (to IEC 60598-1)
- Contains no mercury
- UV filter

Product features

- Average life: 2,000 h
- 100 % dimmable
- Perfect color rendering (Ra: 100)
- Color temperature: 2,900 K


TECHNICAL DATA

Electrical data

| Nominal wattage | 75 W |
|----------------------|---------|
| Construction wattage | 75.00 W |
| Nominal voltage | 230 V |

Photometrical data

| Luminous intensity | 2400 cd |
|---------------------------|------------|
| Light color (designation) | Warm White |
| Color temperature | 2900 K |
| Color rendering index Ra | 100 |
| Light color | 1029 |



349634_HAL_HV_AK

Light technical data

| Beam angle | 30 ° |
|---------------|------|
| Starting time | 0 s |

Dimensions & Weight

| Overall length | 90.50 mm |
|----------------|----------|
| Diameter | 97,0 mm |
| Product weight | 175.00 g |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|---|
| Mercury-free | Yes |
| Design / version | Reflector |
| Product remark | Not suitable for outdoor use or damp conditions / Banned from 1.9.2016 as per EU phase-out plan |

Capabilities

|--|

| Burning position | Any |
|--------------------------------------|-----|
| Country appoiling actor contractions | |

Country-specific categorizations

| ILCOS | HAGS/UB-75-230-E27-97/30 |
|-----------------|--------------------------|
| Order reference | 64845 FL CB 75W |

Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | E27 |
|---|----------|
| Length | 90.50 mm |
| Height | 97,0 mm |
| Width | 97,0 mm |

DOWNLOAD DATA

| Photometric and lighting design files Document | | Document name |
|--|-----------------------------|------------------|
| | Spectral power distribution | 349634_HAL_HV_AK |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4050300338507 | Folding box 1 | 106 mm x 90 mm x 90 mm | 206.00 g | 0.86 dm ³ |
| 4050300338514 | Shipping box 15 | 521 mm x 193 mm x 336 mm | 3540.00 g | 33.79 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.