

PRODUCT DATASHEET HALOLINE PRO 120 W 230 V R7S

HALOLINE® PRO | Double ended halogen lamps with tube base



Areas of application

- General illumination
- Entrance lighting
- Pathway lighting
- Outdoor applications only in suitable luminaires
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Ideal for emphasizing and accentuating the structure of a room

Product benefits

- Brilliant accent lighting
- Direct replacement for standard tubular halogen lamps
- $\,$ Significantly lower \mbox{CO}_2 emissions compared to standard version
- Lower thermal output (compared with the standard reference product)
- No transformer required
- Contains no mercury

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index Ra: 100




TECHNICAL DATA

Electrical data

Nominal wattage	120 W
Construction wattage	120.00 W
Nominal voltage	230 V
Nominal current	520 mA

Photometrical data

Luminous flux	2245 lm
Luminous efficacy	18 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
UV protection	No



349635_HAL_ohne_UVS

Light technical data

Starting time	0 s

Dimensions & Weight

Overall length	118.00 mm
Diameter	12.00 mm
Product weight	7.2 g

Lifespan

Lifespan L70/B50 at 25 °C	2000 h

Additional product data

Base (standard designation)	R7s	
Mercury-free	Yes	
Design / version	Tube	
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required / Technical and light values are subject to be changed	
Capabilities		
Dimmable	Yes	
Burning position	Any	
Certificates & Standards		
Energy efficiency class	G	
Energy consumption	120.00 kWh/1000h	
Country-specific categorizations		
ILCOS HDG-120-230-R7s-114,2		
Order reference	64696 ECO	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	OTHER	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	R7s	
Connected light source (CLS)	No	
Out inected light source (OLO)	No	
Color-tuneable light source	No No	
Color-tuneable light source	No	
Color-tuneable light source Envelope	No No	
Color-tuneable light source Envelope High luminance light source	No No No	
Color-tuneable light source Envelope High luminance light source Anti-glare shield	No No No No	
Color-tuneable light source Envelope High luminance light source Anti-glare shield Correlated colour temperature type	No No No No SINGLE_VALUE	
Color-tuneable light source Envelope High luminance light source Anti-glare shield Correlated colour temperature type Standby power	No No No No SINGLE_VALUE 0 W	
Color-tuneable light source Envelope High luminance light source Anti-glare shield Correlated colour temperature type Standby power Networked standby power for CLS	No No No No SINGLE_VALUE 0 W not applicable	
Color-tuneable light source Envelope High luminance light source Anti-glare shield Correlated colour temperature type Standby power Networked standby power for CLS Claim of equivalent power	No No No No SINGLE_VALUE 0 W not applicable No	

0,437

Chromaticity coordinate x

Chromaticity coordinate y	0,404
Beam angle correspondence	SPHERE_360
Displacement factor	1
EPREL ID	714434,1554002
Model number	AC35303,AC51810,AC51810

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	Traditional lamp

Photometric and lighting design files	Document name
Spectral power distribution	349635_HAL_ohne_UVS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321977670	Folding box	20 mm x 21 mm x 136 mm	11.20 g	0.06 dm ³
4008321977687	Shipping box 20	142 mm x 111 mm x 90 mm	272.00 g	1.42 dm³
4058075308695	Shipping box 15	93 mm x 71 mm x 128 mm	328.00 g	0.85 dm ³
4099854147708	Shipping box 720	440 mm x 347 mm x 385 mm	10342.00 g	58.78 dm ³
4058075308701	Shipping box 60	195 mm x 148 mm x 133 mm	1459.00 g	3.84 dm ³
4052899401280	Shipping box 720			

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

December 11, 2025, 22:43:06 **HALOLINE PRO 120 W 230 V R7S**

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.