

PRODUCT DATASHEET HALOLINE PRO 48 W 240 V R7S

HALOLINE® PRO | Double ended halogen lamps with tube base



Areas of application

- General illumination
- Entrance lighting
- Pathway lighting
- Outdoor applications only in suitable luminaires
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Ideal for emphasizing and accentuating the structure of a room

Product benefits

- Brilliant accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO₂ emissions compared to standard version
- Lower thermal output (compared with the standard reference product)
- No transformer required
- Contains no mercury

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index Ra: 100




TECHNICAL DATA

Electrical data

Nominal wattage	48 W
Construction wattage	48.00 W
Nominal voltage	240 V
Claimed equiv. conventional lamp power	60 W

Photometrical data

Luminous flux	700 lm
Luminous efficacy	14 lm/W
Light color (designation)	Warm White
Color temperature	2800 K
Color rendering index Ra	100
Light color	1028
UV protection	No



349635_HAL_ohne_UVS

Light technical data

	Starting time	0 s
--	---------------	-----

Dimensions & Weight

Overall length	78.00 mm
Diameter	10.00 mm
Product weight	6.1 g

Additional product data

Base (standard designation)	R7s
Mercury-free	Yes

December 15, 2025, 20:37:47 HALOLINE PRO 48 W 240 V R7S

Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required / Technical and light values are subject to be changed
Capabilities	
Dimmable	Yes
Burning position	Any
Certificates & Standards	
Energy efficiency class	G
Energy consumption	48.00 kWh/1000h
Country-specific categorizations	
ILCOS	HDG-48-240-R7s-74,9
Order reference	64684 ECO
Energy labelling regulation data acc EU 2019/2015 Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
	n/5
Connected light source (CLS)	No
	No No
Color-tuneable light source	No
Color-tuneable light source Envelope	No No
Color-tuneable light source Envelope High luminance light source	No No No
Color-tuneable light source Envelope High luminance light source Anti-glare shield	No No No
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power	No No No No No No No
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power Length	No No No No No No 78.00 mm
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power Length Height	No No No No No No T8.00 mm
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power Length Height Width	No No No No No No 10.00 mm 10.00 mm
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power Length Height Width Chromaticity coordinate x	No No No No No No 10.00 mm 10.00 mm 0.444
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power Length Height Width Chromaticity coordinate x Chromaticity coordinate y	No No No No No No No 10.00 mm 10.00 mm 0.444 0.406
Color-tuneable light source Envelope High luminance light source Anti-glare shield Claim of equivalent power Length Height Width Chromaticity coordinate x	No No No No No No 10.00 mm 10.00 mm 0.444

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

DOWNLOAD DATA

Photometric and lighting design files	Document name
Spectral power distribution	349635_HAL_ohne_UVS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321977632	Folding box 1	20 mm x 21 mm x 97 mm	9.10 g	0.04 dm ³
4008321977649	Shipping box 20	103 mm x 111 mm x 90 mm	223.00 g	1.03 dm ³
4052899401099	Shipping box 720			
4099854179310	Shipping box 720	347 mm x 323 mm x 385 mm	8487.00 g	43.15 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

December 15, 2025, 20:37:47 **HALOLINE PRO 48 W 240 V R7S**