

# PRODUCT DATASHEET HALOLINE 1500 W 240 V R7S

HALOLINE® Standard | Double ended halogen lamps with tube base



#### Areas of application

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Outdoor applications only in suitable luminaires

## **Product benefits**

- Brilliant accent light
- No transformer required
- Contains no mercury

### **Product features**

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index Ra: 100
- Color temperature: 3,000 K
- Burning position: p15



December 11, 2025, 16:17:31 HALOLINE 1500 W 240 V R7S


## TECHNICAL DATA

## Electrical data

Nominal wattage	1500.00 W
Construction wattage	1500.00 W
Nominal voltage	240 V

## Photometrical data

Luminous flux	31000 lm
Luminous efficacy	20 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
UV protection	No



349635\_HAL\_ohne\_UVS

# Light technical data

Starting time	0 s
---------------	-----

# Dimensions & Weight

Overall length	254.00 mm
Diameter	12.0 mm
Product weight	18.5 g

## Additional product data

Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube

December 11, 2025, 16:17:32 HALOLINE 1500 W 240 V R7S

Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required
Capabilities	
Dimmable	Yes
Burning position	p15
Certificates & Standards	
Energy efficiency class	G
Energy consumption	1500.00 kWh/1000h
Country-specific categorizations	
ILCOS	HDG-1500-240-R7s-256,1
Order reference	64760 1500W 240
Energy labelling regulation data acc EU 2019/2015  Lighting technology used	OTHER
Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Claim of equivalent power	No
Length	254.00 mm
Height	12.0 mm
Width	12.0 mm
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.406
Beam angle correspondence	SPHERE_360
EPREL ID	714421,1635413
Model number	AC35336,AC54072

# Safety advice

December 11, 2025, 16:17:31 HALOLINE 1500 W 240 V R7S

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	Declarations of conformity	Traditional lamp	
PDF	Declarations of conformity	CE Declaration R7s	
	Photometric and lighting design files	Document name	
	Spectral power distribution	349635_HAL_ohne_UVS	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300209920	Folding box	26 mm x 26 mm x 303 mm	27.50 g	0.20 dm <sup>3</sup>
4050300209937	Shipping box 12	311 mm x 114 mm x 91 mm	400.00 g	3.23 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

December 11, 2025, 16:17:31 HALOLINE 1500 W 240 V R7S