

PRODUCT DATASHEET

DST STICK 11 W/2700 K 220...240 V B22d

OSRAM DULUXSTAR® STICK | Compact fluorescent integrated, stick shape



Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

Product benefits

- Fast return on investment
- Up to 80 % less energy consumption compared with ordinary light bulbs

Product features

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	220...240 V
Nominal current	110 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor λ	≥ 0.55

Photometrical data

Luminous flux	600 lm
Color temperature	2700 K
Color rendering index Ra	≥ 80
Light color	827

Light technical data

Starting time	≤ 0.3 s
---------------	--------------

Dimensions & Weight

Overall length	122.00 mm
Diameter	41.00 mm
Maximum diameter	41 mm
Product weight	59.00 g

Lifespan

Number of switching cycles	≥ 10000
----------------------------	--------------

Additional product data

Base (standard designation)	B22d
Mercury content	2.0 mg
Mercury-free	No

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

Order reference	DSTAR 11W/827 2
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	122.00 mm
Height	41.00 mm
Width	41.00 mm

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp
- Not for use with external dimmers or electronic switches.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899927414	Folding box 1	45 mm x 45 mm x 121 mm	102.00 g	0.25 dm ³
4058075076617	Bundle 10	215 mm x 86 mm x 129 mm	742.00 g	2.39 dm ³
4058075076624	Shipping box 10	226 mm x 95 mm x 146 mm	833.00 g	3.13 dm ³
4052899449473	Shipping box 10	226 mm x 95 mm x 146 mm	831.00 g	3.13 dm ³
4058075021686	Shipping box 50	225 mm x 225 mm x 279 mm	3977.00 g	14.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.