

## PRODUCT DATASHEET

### DULUX T/E PLUS 42 W/3000 K 135 V GX24q-4

OSRAM DULUX® T/E PLUS | CFLni, 3 tubes, with 4-pin base for ECG operation



#### Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industrial lighting

#### Product benefits

- Improved maintenance

#### Product features

- Good color rendering index
- Dimmable (3...100 %)
- Short and compact pin-base lamp with triple-turn tubes
- Single-ended four-pin plug-in GX24q base with shortened base casing



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	42 W
Construction wattage	43.00 W
Nominal voltage	135 V
Nominal current	320 mA
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

**Photometrical data**

Luminous flux	3200 lm
Color temperature	3000 K
Color rendering index Ra	≥80
Light color	830
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

**Dimensions & Weight**

Overall length	167.00 mm
Length acc. to IEC standard	155 mm
Length with base excl. base pins/connection	152,00 mm
Diameter	12.00 mm
Product weight	70.00 g

**Additional product data**

Base (standard designation)	GX24q-4
Mercury content	1.7 mg

**Country-specific categorizations**

Order reference	DULUX T/E 42W/8
-----------------	-----------------

**Energy labelling regulation data acc EU 2019/2015**

Light source cap-type (or other electric interface)	GX24q-4
Length	169.00 mm
Height	12.00 mm
Width	12.00 mm

---

**EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic control gear

---

### Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

---

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321581372	Folding box 1	45 mm x 48 mm x 173 mm	93.00 g	0.37 dm <sup>3</sup>
4008321581389	Shipping box 50	504 mm x 239 mm x 188 mm	5084.00 g	22.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.