

PRODUCT DATASHEET DULUX D 18 W/4000 K G24d-2

OSRAM DULUX® D | CFLni, 2 tubes, with 2-pin base for CCG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Improved maintenance

Product features

- Good color rendering index
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base



TECHNICAL DATA

Electrical data

| Nominal wattage | 18 W |
|----------------------|---------|
| Construction wattage | 18.00 W |

Photometrical data

| Luminous flux | 1200 lm |
|------------------------------------|---------|
| Color temperature | 4000 K |
| Color rendering index Ra | 8089 |
| Light color | 840 |
| Rated LLMF at 2,000 h | 0.85 |
| Rated LLMF at 4,000 h | 0.78 |
| Rated LLMF at 6,000 h | 0.72 |
| Rated LLMF at 8,000 h | 0.68 |
| Rated lamp efficacy (standard co.) | 67 lm/W |

Dimensions & Weight

| Overall length | 153.00 mm |
|----------------|-----------|
| Diameter | 11.00 mm |
| Product weight | 45.76 g |

Temperatures & operating conditions

| Rated ambient temp.w.max.luminous | 25.0 °C |
|-----------------------------------|---------|
|-----------------------------------|---------|

Lifespan

| Rated lamp survival factor at 2,000 h | 0.99 |
|---------------------------------------|-------|
| Rated lamp survival factor at 4,000 h | 0.94 |
| Rated lamp survival factor at 6,000 h | 0.84 |
| Rated lamp survival factor at 8,000 h | 0.69 |
| Operation mode LLMF/LSF | 50 Hz |

Additional product data

| Base (standard designation) | G24d-2 |
|-----------------------------|--------|
| Mercury content | 1.4 mg |

Capabilities

Country-specific categorizations

| Order reference DULUX D 18W/840 | |
|---------------------------------|--|
|---------------------------------|--|

Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | G24d-2 |
|---|-----------|
| Length | 153.00 mm |
| Height | 11.00 mm |
| Width | 11.00 mm |

EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321830890 | Folding box 1 | 36 mm x 36 mm x 160 mm | 62.80 g | 0.21 dm ³ |
| 4008321830906 | Shipping box 10 | 187 mm x 81 mm x 175 mm | 703.00 g | 2.65 dm ³ |
| 4058075497993 | Shipping box 50 | 368 mm x 184 mm x 175 mm | 3080.00 g | 11.85 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.