

PRODUCT DATASHEET DULUX D/E 18 W/827

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Improved maintenance

Product features

- Good color rendering index
- Dimmable (3...100 %)
- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base






TECHNICAL DATA

Electrical data


Nominal wattage	18 W
Construction wattage	18.70 W
Nominal voltage	100 V
Nominal current	0.22 A

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	64 lm/W
Light color (designation)	LUMILUX INTERNA
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.84
Rated LLMF at 6,000 h	0.83
Rated LLMF at 8,000 h	0.81
Rated LLMF at 12,000 h	0.79
Rated LLMF at 16,000 h	0.78
Rated LLMF at 20,000 h	0.77



Dimensions & Weight



Overall length	146.00 mm
Length with base excl. base pins/connection	130,00 mm
Diameter	12.0 mm
Tube diameter	12 mm
Product weight	37.5 g

Temperatures & operating conditions

	+40 °C
--	--------

Lifespan

Service life	13000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.81
Rated lamp survival factor at 20,000 h	0.50
Lifespan B50	20000 h

Additional product data

Base (standard designation)	G24q-2
Mercury content	1.6 mg

Capabilities

Dimmable	Yes		
Certificates & Standards			
Energy efficiency class	G		
Energy consumption	19.00 kWh/1000h		
Country-specific categorizations			
ILCOS	FSQH-18/827-/P/-G24q-2		
Order reference	DULUX D/E 18W/8		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	CFLNI		
Non-directional or directional	NDLS		
Mains or non-mains	NMLS		
Light source cap-type (or other electric interface)	G24q-2		
Connected light source (CLS)	No		
Color-tuneable light source	No		
Envelope	No		
High luminance light source	No		

No

No

SINGLE_VALUE

146.00 mm 12.0 mm

12.0 mm

0,455

0,415

546447

AC34222

SPHERE_360

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

Safety advice

Anti-glare shield

Length

Height Width

EPREL ID

Model number

Correlated colour temperature type

Claim of equivalent power

Chromaticity coordinate x

Chromaticity coordinate y

Beam angle correspondence

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077878-EN-00 - DULUX D
PDF	Certificates	EAC N RU D-DE.MU62.B.00933_20 06.03.2020-05.03.2025 Prommash Test - CFLpin
PDF	Certificates	EAC RU C-DE.HA46.B.01131_21 21.05.2021-20.05.2026 Expert Certification - CFLpin

Photometric and lighting design files	Document name	
Spectral power distribution	349636_FL_827	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300012148	Folding box 1	36 mm x 36 mm x 160 mm	55.57 g	0.21 dm ³
4050300325996	Shipping box 10	187 mm x 81 mm x 175 mm	609.17 g	2.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.