

# PRODUCT DATASHEET DULUX D/E 13 W/4000 K G24q-1

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



#### Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

#### Product benefits

- Extremly economical
- Good quality of light

## **Product features**

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



# TECHNICAL DATA

# Electrical data

Nominal wattage	13 W
Construction wattage	13.00 W

## Photometrical data

Luminous flux	900 lm
Luminous flux at 25 °C	900 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.84
Rated LLMF at 6,000 h	0.83
Rated LLMF at 8,000 h	0.81
Rated lamp efficacy (standard co.)	69 lm/W

# Dimensions & Weight

Overall length	129.00 mm
Length with base excl. base pins/connection	115,00 mm
Diameter	12.00 mm
Maximum diameter	11 mm
Product weight	41.00 g

# Temperatures & operating conditions

Rated ambient temp.w.max.luminous	25.0 °C

# Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	HF

# Additional product data

Base (standard designation)	G24q-1
Mercury content	1.3 mg

# Capabilities

Suitable for indoor	Yes
---------------------	-----

# Certificates & Standards

Energy efficiency class	А
Energy consumption	14.30 kWh/1000h

# Country-specific categorizations

ILCOS	FSQ-13/40/1B-E-G24q-1
Order reference	DULUX D/E 13W/8

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24q-1
Length	131.00 mm
Height	12.00 mm
Width	12.00 mm

## **EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic control gear

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	334200_Technical guide - OSRAM DULUX pin-base

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830357	Folding box 1	35 mm x 35 mm x 145 mm	49.00 g	0.18 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830364	Shipping box 10	187 mm x 81 mm x 163 mm	720.00 g	2.47 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.