

PRODUCT DATASHEET HQI-TS 250 W/NDL UVS

POWERSTAR HQI®-TS | Metal halide lamps with quartz technology for enclosed luminaires



Areas of application

- Foyers, reception areas
- Factory and hall lighting with low-cost installations
- Exhibition halls and trade fairs
- Sports halls and multi-purpose halls
- Pedestrian zones, public squares
- Parks and gardens
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- High efficiency
- Uniform distribution of light
- Good to excellent color rendering
- Hot restrike capable
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- POWERSTAR® quartz technology
- Light colors: warm white (WDL), neutral white (NDL), daylight (D)





TECHNICAL DATA


Electrical data

Nominal wattage	250 W
Construction wattage	250.00 W
Nominal voltage	91 V
Ignition voltage	4.0/25 kVp ¹⁾
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	3.04 A
PFC capacitor at 50 Hz	32 µF

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	20000 lm
Luminous efficacy	80 lm/W
Light color (designation)	Neutral White DE LUXE
Color temperature	4200 K
Color rendering index Ra	88
Light color	842
Rated LLMF at 2,000 h	0.80
Rated LLMF at 4,000 h	0.75
Rated LLMF at 6,000 h	0.65
Rated LLMF at 8,000 h	0.55
Rated LLMF at 12,000 h	0.50
UV protection	Yes



384074_HQI_TS_NDL

Dimensions & Weight

Quayall lag eth	101.00 mm
Overall length	161.60 mm
Light center length (LCL)	81,0 mm
Diameter	25,0 mm
Product weight	52.00 g
Temperatures & operating conditions	
Maximum permitted outer bulb temperature	650 °C
Maximum permitted pinch temperature	300 °C
Lifespan	
Rated lamp survival factor at 2,000 h	0.95
Rated lamp survival factor at 4,000 h	0.90
Rated lamp survival factor at 6,000 h	0.85
Rated lamp survival factor at 8,000 h	0.80
Rated lamp survival factor at 12,000 h	0.50
Lifespan B50	12000 h
Additional product data	
Base (standard designation)	Fc2
Mercury content	12.0 mg
Design / version	Clear
Capabilities	
Dimmable	No
Burning position	P45
Enclosed luminaire required	Yes
Hot restart	Yes
Certificates & Standards	
Energy efficiency class	G
Energy consumption	241.00 kWh/1000h
Country-specific categorizations	
ILCOS	MD/UB-250/842-H/E/SL-Fc2-25/162/H
Order reference	HQI-TS 250W/NDL
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	MH

Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	Fc2
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	161.60 mm
Height	25,0 mm
Width	25,0 mm
Chromaticity coordinate x	0,370
Chromaticity coordinate y	0,365
Beam angle correspondence	SPHERE_360
EPREL ID	666230
Model number	AM42361

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	High Intensity Discharge Lamp UI	
PDF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4072118-EN-12 - HQI	
PDF	Certificates	EAC RU C-DE.AYA46.B.16106_20 13.10.2020-12.10.2025 Rostest-Moskva - MH double capped	
PDF	Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH	
	Photometric and lighting design	n files Document name	

Photometric and lighting design files	Document name	
Spectral power distribution	384074_HQI_TS_NDL	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321766878	Sleeve 1	52 mm x 52 mm x 260 mm	92.00 g	0.70 dm ³
4008321766885	Shipping box 12	216 mm x 166 mm x 272 mm	984.00 g	9.75 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.