

# PRODUCT DATASHEET HQI-E 250 W/D PRO

POWERSTAR HQI®-E coated 250...400 W | Metal halide lamps with quartz technology for enclosed luminaires



#### Areas of application

- Factories and workshops
- Exhibition halls and trade fairs
- Sports halls and multi-purpose halls
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

#### **Product benefits**

- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

#### **Product features**

- POWERSTAR® quartz technology
- Light colors: neutral white (NDL), daylight (D)





## TECHNICAL DATA


## Electrical data

Nominal wattage	250 W
Construction wattage	260.00 W
Nominal voltage	105 V
Ignition voltage	4.0/5.0 kVp <sup>1)</sup>
Operating mode	Conventional control gear (CCG) and ignitor
Nominal current	3000 mA
PFC capacitor at 50 Hz	32 µF

<sup>1)</sup> Minimum / Maximum

## Photometrical data

Luminous flux	18000 lm
Luminous efficacy	69 lm/W
Color temperature	5500 K
Color rendering index Ra	≤ 90
Light color	955
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.87
Rated LLMF at 8,000 h	0.85
Rated LLMF at 12,000 h	0.81
UV protection	Yes



384076\_HQI\_T\_D\_PRO

## Dimensions & Weight

Overall length	226.00 mm
----------------	-----------

Diameter	90,0 mm	
Product weight	160.00 g	
Femperatures & operating conditions		
ximum permitted outer bulb temperature 400 °C		
Maximum permitted base edge temperature	250 °C	
Lifespan		
Rated lamp survival factor at 2,000 h	0.96	
Rated lamp survival factor at 4,000 h	0.94	
Rated lamp survival factor at 6,000 h	0.93	
Rated lamp survival factor at 8,000 h	0.88	
Rated lamp survival factor at 12,000 h	0.81	
Lifespan B50	16000 h	
Additional product data		
Base (standard designation)	E40	
Mercury content	21.0 mg	
Design / version	Coated	
Capabilities		
Dimmable	No	
Burning position	Any	
Enclosed luminaire required	Yes	
Hot restart	No	
Certificates & Standards		
Energy efficiency class	G	
Energy consumption	260.00 kWh/1000h	
Country-specific categorizations		
ILCOS	ME/UB-250/952-H/E/SL-E40-91/226	
Order reference	HQI-E 250W/D PR	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	MH	
Non-directional or directional	NDLS	
Mains or non-mains	NMLS	

Light source cap-type (or other electric interface)	E40
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	NON_CLEAR
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	226.00 mm
Height	90,0 mm
Width	90,0 mm
Chromaticity coordinate x	0,340
Chromaticity coordinate y	0,345
Beam angle correspondence	SPHERE_360
EPREL ID	546553
Model number	AC34327

## Safety advice

- Do not stare at the operating light source: The luminaire should be positioned so that prolonged staring into the luminaire at a distance closer that 4 m is not expected.
- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	High Intensity Discharge Lamp UI
PDF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077886-EN-00 - HQI
PDF	Certificates	EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
PDF	Certificates	EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH

Photometric and lighting design files	Document name	
Spectral power distribution	384076_HQI_T_D_PRO	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321677907	Round wrap 1	95 mm x 95 mm x 240 mm	191.00 g	2.17 dm <sup>3</sup>
4008321677914	Shipping box 12	426 mm x 331 mm x 252 mm	2879.00 g	35.53 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.