

## PRODUCT DATASHEET NAV-E 70 W SUPER 4Y

VIALOX® NAV®-E SUPER 4Y® | High-pressure sodium vapor lamps for open and enclosed luminaires



### Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

### Product benefits

- Very high luminous efficacy
- Very good luminous flux maintenance throughout the life of the lamp
- Energy savings of up to 50 % when replacing mercury vapor lamps (HQL)
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs

### Product features

- Lamp survival factor: 95 % after 16,000 h burning time
- Lamp maintenance factor:  $\geq 80$  % after 16,000 h burning time (according to DIN 13201)
- Service lifetime: 4 years (at approx. 11 h/day)
- Dimmable on conventional control gears and electronic control gears



TECHNICAL DATA

Electrical data

Nominal wattage	70 W
Construction wattage	75.40 W
Nominal voltage	90 V
Ignition voltage	1.8/5.0 kVp <sup>1)</sup>
Operating mode	Conventional control gear (CCG) and ignitor, Electronic control gear (ECG)
Nominal current	970 mA
PFC capacitor at 50 Hz	12 µF

1) Minimum / Maximum

Photometrical data

Luminous flux	6600 lm
Luminous efficacy	88 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.91
Rated LLMF at 6,000 h	0.90
Rated LLMF at 8,000 h	0.89
Rated LLMF at 12,000 h	0.88
Rated LLMF at 16,000 h	0.86
Rated LLMF at 20,000 h	0.85
UV protection	No



384084\_NAV\_SUPER\_4Y

### Dimensions & Weight

Overall length	155.00 mm
Diameter	71.00 mm
Product weight	50.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	310 °C
Maximum permitted base edge temperature	210 °C

### Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.98
Rated lamp survival factor at 8,000 h	0.97
Rated lamp survival factor at 12,000 h	0.96
Rated lamp survival factor at 16,000	0.95
Rated lamp survival factor at 20,000 h	0.90
Lifespan B10	20000 h
Lifespan B5	16000 h
Lifespan B50	30000 h

### Additional product data

Base (standard designation)	E27
Mercury content	10.8 mg
Design / version	Coated
Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable

### Capabilities

Dimmable	Yes <sup>1)</sup>
Burning position	Any
Enclosed luminaire required	No

<sup>1)</sup> In combination with POWERTRONIC PTo

### Certificates & Standards

Energy efficiency class	G
Energy consumption	76.00 kWh/1000h

## Country-specific categorizations

ILCOS	SE-70-H/E/SL-E27-71/156
Order reference	NAV-E 70W SUPER

## Energy labelling regulation data acc EU 2019/2015

Lighting technology used	HPS
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	155.00 mm
Height	71.00 mm
Width	71.00 mm
Chromaticity coordinate x	0,535
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546590
Model number	AC34383,AC34383

## Safety advice

- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Protect from spray water.

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	High Intensity Discharge Lamp UI
	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077887-EN-00 - HPS

Documents and certificates		Document name
	Certificates	EAC RU C-DE.AYA46.B.85891 29.06.2018-28.06.2023 ROSTEST-Moskva - HPS
	Certificates	EAC N RU D-DE.MU62.B.00936_20 06.03.2020-05.03.2025 Prommash Test - HPS
Photometric and lighting design files		Document name
	Spectral power distribution	384084_NAV_SUPER_4Y

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321356048	Round wrap 1	75 mm x 75 mm x 165 mm	80.00 g	0.93 dm <sup>3</sup>
4008321356055	Shipping box 24	360 mm x 285 mm x 355 mm	1967.00 g	36.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.