

PRODUCT DATASHEET

NAV-E 68 W E27

VIALOX® NAV®-E Plug-in | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Luminaires that use mercury vapor lamps HQL® 80 W, 125 W, 250 W, 400 W
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- No modifications to existing luminaire components required



TECHNICAL DATA

Electrical data

| | |
|------------------------|---|
| Nominal wattage | 68 W |
| Construction wattage | 70.00 W |
| Nominal voltage | 102 V |
| Ignition voltage | 0.198 kVp |
| Operating mode | Conventional control gear (CCG) without ignitor |
| Nominal current | 850 mA |
| PFC capacitor at 50 Hz | 8 µF |

Photometrical data

| | |
|--------------------------|---------|
| Luminous flux | 5400 lm |
| Luminous efficacy | 77 lm/W |
| Color temperature | 2000 K |
| Color rendering index Ra | ≤25 |
| Light color | 220 |
| Rated LLMF at 2,000 h | 0.92 |
| Rated LLMF at 4,000 h | 0.88 |
| Rated LLMF at 6,000 h | 0.85 |
| Rated LLMF at 8,000 h | 0.84 |
| Rated LLMF at 12,000 h | 0.83 |
| Rated LLMF at 16,000 h | 0.80 |
| Rated LLMF at 20,000 h | 0.75 |
| UV protection | No |



384084_NAV_SUPER_4Y

Dimensions & Weight

| | |
|----------------|-----------|
| Overall length | 155.00 mm |
|----------------|-----------|

| | |
|----------------|---------|
| Diameter | 71 mm |
| Product weight | 50.00 g |

Temperatures & operating conditions

| | |
|--|--------|
| Maximum permitted outer bulb temperature | 400 °C |
| Maximum permitted base edge temperature | 210 °C |

Lifespan

| | |
|--|---------|
| Rated lamp survival factor at 2,000 h | 0.98 |
| Rated lamp survival factor at 4,000 h | 0.98 |
| Rated lamp survival factor at 6,000 h | 0.97 |
| Rated lamp survival factor at 8,000 h | 0.96 |
| Rated lamp survival factor at 12,000 h | 0.90 |
| Rated lamp survival factor at 16,000 | 0.80 |
| Rated lamp survival factor at 20,000 h | 0.50 |
| Lifespan B10 | 12000 h |
| Lifespan B5 | 9000 h |
| Lifespan B50 | 20000 h |

Additional product data

| | |
|-----------------------------|---------|
| Base (standard designation) | E27 |
| Mercury content | 14.7 mg |
| Design / version | Coated |

Capabilities

| | |
|-----------------------------|-----|
| Dimmable | No |
| Burning position | Any |
| Enclosed luminaire required | No |

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | G |
| Energy consumption | 70.00 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|-------------------------|
| ILCOS | SEQ-68-H/I/S-E27-71/152 |
| Order reference | NAV-E 68W E27 |

Energy labelling regulation data acc EU 2019/2015

| | |
|---|-----------------|
| Lighting technology used | HPS |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | E27 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | SECOND |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 155.00 mm |
| Height | 71 mm |
| Width | 71 mm |
| Chromaticity coordinate x | 0,535 |
| Chromaticity coordinate y | 0,420 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 546568 |
| Model number | AC34360,AC34360 |






Safety advice

- Control gear must be suitable for the higher operating current of the NAV® Plug-in lamps. The maximum permissible winding temperature as defined in VDE and IEC specifications must not be exceeded. In case of doubt, consult the manufacturer of the luminaire or control gear.
- Do not stare at the operating light source: The luminaire should be positioned so that prolonged staring into the luminaire at a distance closer than 4 m is not expected.
- Disconnect mains before installation.
- Must not be used if outer bulb is defective.
- Protect from spray water.

ADDITIONAL PRODUCT INFORMATION

- Control gear must be suitable for the higher operating current of the NAV® Plug-in lamps. The maximum permissible winding temperature as defined in VDE and IEC specifications must not be exceeded. In case of doubt, consult the manufacturer of the luminaire or control gear.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|---|--|---|
|  | User instruction / safety instructions | High Intensity Discharge Lamp UI |
|  | Declarations of conformity | EC Declaration of Conformity - 2021 9C1-4077887-EN-00 - HPS |
|  | Certificates | EAC RU C-DE.AYA46.B.85891 29.06.2018-28.06.2023 ROSTEST-Moskva - HPS |
|  | Certificates | EAC N RU D-DE.MU62.B.00936_20 06.03.2020-05.03.2025 Prommash Test - HPS |
| Photometric and lighting design files | | Document name |
|  | Spectral power distribution | 384084_NAV_SUPER_4Y |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008321345462 | Round wrap 1 | 75 mm x 75 mm x 165 mm | 83.00 g | 0.93 dm ³ |
| 4008321345479 | Shipping box 24 | 360 mm x 285 mm x 355 mm | 2039.00 g | 36.42 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.