

## PRODUCT DATASHEET

### HO 49 W/865

LUMILUX® T5 HO | Tubular fluorescent lamps 16 mm, high output, with G5 base



#### Areas of application

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks
- Outdoor applications only in suitable luminaires

#### Product benefits

- Up to 20 % more economical than LUMILUX® T8

#### Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	49 W
Construction wattage	49.00 W
Nominal voltage	195 V
Rated lamp efficacy (HF data 25 °C)	79

Photometrical data

Luminous flux	4100 lm
Luminous efficacy	83 lm/W
Luminous flux at 25 °C	4100 lm
Luminous flux at 35 °C	4600 lm
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.93
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	79



349641\_FL\_865

Dimensions & Weight

Overall length	1449.00 mm
----------------	------------

Length with base excl. base pins/connection	1449 mm
Diameter	16,0 mm
Tube diameter	16 mm
Product weight	121.00 g

### Temperatures & operating conditions

Rated ambient temp.w.max.luminous	35.0 °C
-----------------------------------	---------

### Lifespan

Service life	19000 h <sup>1)</sup>
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.97
Rated lamp survival factor at 20,000 h	0.85
Operation mode LLMF/LSF	HF

<sup>1)</sup> With preheat ECG

### Additional product data

Base (standard designation)	G5
Mercury content	1.7 mg
Product remark	Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C

### Capabilities

Suitable for indoor	Yes
Dimmable	Yes

### Certificates & Standards

Energy efficiency class	G
Energy consumption	54.12 kWh/1000h

### Country-specific categorizations

ILCOS	FDH-49/865-L/P/-G5-16/1449
-------	----------------------------

Order reference	HO 49W/865
-----------------	------------


### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LFL_T5_HO
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G5
Envelope	No
Length	1449.00 mm
Height	16,0 mm
Width	16,0 mm
Beam angle correspondence	SPHERE_360

### Safety advice

– In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

### DOWNLOAD DATA

Photometric and lighting design files		Document name
	Spectral power distribution	349641_FL_865

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321110732	Unpacked 1	1,463 mm x 15 mm x 18 mm	137.00 g	0.40 dm <sup>3</sup>
4008321110749	Shipping box 40	1,496 mm x 199 mm x 87 mm	5422.00 g	25.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.