

PRODUCT DATASHEET HE SL 14 W/840

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency






TECHNICAL DATA

Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	86

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	85 lm/W
Luminous flux at 25 °C	1200 lm
Luminous flux at 35 °C	1350 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	86



Dimensions & Weight

Overall length	549.00 mm
o voram longan	0.10100.11111

Length with base excl. base pins/connection 549,00 mm Diameter 16,0 mm Tube diameter 16 mm Maximum diameter 16 mm Product weight 45.00 g Temperatures & operating conditions Rated ambient temp.w.max.luminous 35.0 °C Lifespan	
Tube diameter 16 mm Maximum diameter 16 mm Product weight 45.00 g Temperatures & operating conditions Rated ambient temp.w.max.luminous 35.0 °C	
Maximum diameter 16 mm Product weight 45.00 g Temperatures & operating conditions Rated ambient temp.w.max.luminous 35.0 °C	
Product weight 45.00 g Temperatures & operating conditions Rated ambient temp.w.max.luminous 35.0 °C	
Temperatures & operating conditions Rated ambient temp.w.max.luminous 35.0 °C	
Rated ambient temp.w.max.luminous 35.0 °C	
Lifespan	
Rated lamp survival factor at 2,000 h 0.99	
Rated lamp survival factor at 4,000 h 0.99	
Rated lamp survival factor at 6,000 h 0.99	
Rated lamp survival factor at 8,000 h 0.99	
Rated lamp survival factor at 12,000 h 0.99	
Rated lamp survival factor at 16,000 0.90	
Rated lamp survival factor at 20,000 h 0.50	
Operation mode LLMF/LSF HF	
Additional product data	
Base (standard designation) G5	
Mercury content 1.2 mg	
Capabilities	
Suitable for indoor Yes	
Certificates & Standards	
Energy efficiency class A+	
Energy consumption 15.40 kWh/1000h	
Country-specific categorizations	
Order reference HE 14W/840 SL	
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface) G5	
Length 549.00 mm	
Height 16,0 mm	

Width 16,0 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
Spectral power distribution	349615_FL_840

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321339393	Sleeve 1	563 mm x 18 mm x 18 mm	55.00 g	0.18 dm ³
4008321339409	Shipping box 50	600 mm x 204 mm x 123 mm	2992.00 g	15.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.