Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

# PRODUCT DATASHEET HE SL 35 W/840

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency



# **Oops! An Error Occurred**

The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.


#### TECHNICAL DATA

### Electrical data

Nominal wattage	35 W
Construction wattage	35.00 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	94

#### Photometrical data

Luminous flux	3320 lm
Luminous efficacy	94 lm/W
Luminous flux at 25 °C	3320 lm
Luminous flux at 35 °C	3650 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	94



## Dimensions & Weight

Overall length 1449.00 mm

# **Oops! An Error Occurred**

# The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

Length with base excl. base pins/connection	1449 mm			
Diameter	16,0 mm			
Tube diameter	16 mm			
Maximum diameter	16 mm			
Product weight	115.00 g			
Temperatures & operating conditions				
Rated ambient temp.w.max.luminous	35.0 °C			
Lifespan				
Rated lamp survival factor at 2,000 h	0.99			
Rated lamp survival factor at 4,000 h	0.99			
Rated lamp survival factor at 6,000 h	0.99			
Rated lamp survival factor at 8,000 h	0.99			
Rated lamp survival factor at 12,000 h	0.99			
Rated lamp survival factor at 16,000	0.90			
Rated lamp survival factor at 20,000 h	0.50			
Operation mode LLMF/LSF	HF			
Additional product data				
Base (standard designation)	G5			
Mercury content	1.2 mg			
Capabilities				
Suitable for indoor	Yes			
Certificates & Standards				
Energy efficiency class	A+			
Energy consumption	39.05 kWh/1000h			
Country-specific categorizations				
Order reference	HE 35W/840 SL			
Energy labelling regulation data acc EU 2019/2015				
Light source cap-type (or other electric interface)	G5			
Length	1449.00 mm			

16,0 mm

# **Oops! An Error Occurred**

Height

# The server returned a "500 Internal Server Error".

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

#### **DOWNLOAD DATA**

Photometric and lighting design files	Document name
Spectral power distribution	349615_FL_840

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321335685	Sleeve 1	1,464 mm x 18 mm x 18 mm	138.00 g	0.47 dm <sup>3</sup>
4052899046900	Shipping box 20	1,511 mm x 104 mm x 88 mm	3498.00 g	13.83 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# **Oops! An Error Occurred**

The server returned a "500 Internal Server Error".