

# PRODUCT DATASHEET L 18W / 3000K 2PK

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



#### Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

## **Product benefits**

- Proven lamp technology

#### **Product features**

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



## TECHNICAL DATA

## Electrical data

Nominal wattage	18 W	
Construction wattage	18.00 W	
Nominal voltage	220 V	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

# Photometrical data

Luminous flux at 25 °C	1350 lm	
Color rendering index Ra	> 80	
Light color	8	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

# Dimensions & Weight

Overall length	590.00 mm
Length with base excl. base pins/connection	590,00 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	85.4 g

# Lifespan

Service life	18000 h <sup>1)</sup>

<sup>1)</sup> With preheat ECG

# Additional product data

Base (standard designation)	G13
Mercury content	4.0 mg

## Capabilities

Dimmable	Yes
----------	-----

## Country-specific categorizations

Order reference	L 18W/830LUMILU
-----------------	-----------------

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
---	-----

Length	590.00 mm
Height	26.00 mm
Width	26.00 mm

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321660244	Sleeve 2	649 mm x 54 mm x 27 mm	211.83 g	0.95 dm <sup>3</sup>
4008321660251	Shipping box 24	659 mm x 173 mm x 124 mm	2782.00 g	14.14 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.