

# PRODUCT DATASHEET L 58 W/830

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



#### Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

#### Product benefits

- Proven lamp technology

#### **Product features**

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable






# TECHNICAL DATA

# Electrical data

Nominal wattage	58 W
Construction wattage	58.00 W

#### Photometrical data

Luminous flux	5200 lm
Luminous efficacy	90 lm/W
Luminous flux at 25 °C	5200 lm
Light color (designation)	LUMILUX Warm White
Color temperature	3000 K
Color rendering index Ra	≥80
Light color	830
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.94
Rated LLMF at 6,000 h	0.93
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (standard co.)	90 lm/W



# Dimensions & Weight

Overall length	1500.00 mm
Length with base excl. base pins/connection	1500 mm
Diameter	26.00 mm
Tube diameter	26 mm

Maximum diameter	26 mm	
Product weight	184.00 g	
Froduct Weight	104.00 g	
Femperatures & operating conditions		
Rated ambient temp.w.max.luminous	25.0 °C	
ifespan		
Service life	18000 h <sup>1)</sup>	
Rated lamp survival factor at 2,000 h	0.99	
Rated lamp survival factor at 4,000 h	0.99	
Rated lamp survival factor at 6,000 h	0.99	
Rated lamp survival factor at 8,000 h	0.99	
Rated lamp survival factor at 12,000 h	0.99	
Rated lamp survival factor at 16,000	0.99	
Rated lamp survival factor at 20,000 h	0.50	
0 " 1 11 15 16 16		
Operation mode LLMF/LSF  With preheat ECG	HF	
With preheat ECG Additional product data	HF G13	
) With preheat ECG		
Additional product data  Base (standard designation)  Mercury content	G13	
Additional product data  Base (standard designation)	G13	
Additional product data  Base (standard designation)  Mercury content  Capabilities	G13 2.5 mg	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor  Dimmable	G13 2.5 mg  Yes	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor	G13 2.5 mg  Yes	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor  Dimmable  Certificates & Standards	G13 2.5 mg  Yes Yes	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor  Dimmable  Certificates & Standards  Energy efficiency class	G13 2.5 mg  Yes Yes A	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor  Dimmable  Certificates & Standards  Energy efficiency class  Energy consumption	G13 2.5 mg  Yes Yes A	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor  Dimmable  Certificates & Standards  Energy efficiency class  Energy consumption  Country-specific categorizations	G13 2.5 mg  Yes  Yes  A  67.10 kWh/1000h	
Additional product data  Base (standard designation)  Mercury content  Capabilities  Suitable for indoor  Dimmable  Certificates & Standards  Energy efficiency class  Energy consumption  Country-specific categorizations  ILCOS	G13 2.5 mg  Yes  Yes  A  67.10 kWh/1000h  FD-58/830-E-G13-26/1500	

Length	1500.00 mm
Height	26.00 mm
Width	26.00 mm

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Certificates	335187_Manufacturer's declaration Lamps LUMILUX L58 W with QTP5 2x54

Photometric and lighting design files	Document name
Spectral power distribution	349617_FL_830

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300470382	Unpacked 1	1,140 mm x 21 mm x 23 mm	210.75 g	0.55 dm <sup>3</sup>
4050300470399	Shipping box 30	1,295 mm x 456 mm x 206 mm	7243.00 g	121.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.