

PRODUCT DATASHEET L 15 W/827

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable






TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	14.90 W
Nominal voltage	55 V
Nominal current	0.31 A

Photometrical data

Luminous flux	950 lm
Luminous efficacy	64 lm/W
Light color (designation)	LUMILUX INTERNA
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.94
Rated LLMF at 6,000 h	0.93
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.96



Dimensions & Weight

Overall length	451.60 mm
Length with base excl. base pins/connection	438,00 mm
Diameter	26,0 mm
Tube diameter	26 mm

Product weight	60.00 g	
ifespan		
ice life 16000 h 1)		
Rated lamp survival factor at 2,000 h	0.99	
Rated lamp survival factor at 4,000 h	0.99	
Rated lamp survival factor at 6,000 h	0.99	
Rated lamp survival factor at 8,000 h	0.99	
Rated lamp survival factor at 12,000 h	0.99	
Rated lamp survival factor at 16,000	0.90	
Rated lamp survival factor at 20,000 h	0.50	
Lifespan B50	20000 h	
) With preheat ECG		
additional product data		
Base (standard designation)	G13	
Mercury content	3.0 mg	
Capabilities		
Dimmable	Yes	
Certificates & Standards		
Energy efficiency class	G	
Energy consumption	15.00 kWh/1000h	
Country-specific categorizations		
ILCOS	FD-15/827-E-G13-26/438	
Order reference	L 15W/827	
nergy labelling regulation data acc EU 2019/2015		
Lighting technology used	OTHER_FL	
Non-directional or directional	NDLS	
Mains or non-mains	NMLS	
Light source cap-type (or other electric interface)	G13	
Connected light source (CLS)	No	
Color-tuneable light source	No	

Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	451.60 mm
Height	26,0 mm
Width	26,0 mm
Chromaticity coordinate x	0,463
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546355,1215991
Model number	AC34142,AC42499

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4071456-EN-01 - T8
PDF	Declarations of conformity	L 15W T8

Photometric and lighting design files	Document name
Spectral power distribution	349636_FL_827

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300446042	Sleeve 1	27 mm x 28 mm x 453 mm	75.00 g	0.34 dm ³
4050300446059	Shipping box 25	474 mm x 150 mm x 155 mm	2034.00 g	11.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.