

PRODUCT DATASHEET

L 18 W/930

LUMILUX® DE LUXE T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Ideal where color rendering is an important factor
- Public buildings
- Shops
- Supermarkets and department stores
- Industry

Product benefits

- Excellent color rendering
- Natural colors
- Available in many different light colors (3,000...6,500 K) for various applications
- High luminous flux

Product features

- Very good color rendering group: 1A ($R_a: \geq 90$)
- Long service life: up to 16,000 h (with preheat ECG)
- Dimmable




TECHNICAL DATA

Electrical data

Nominal wattage	18 W
Construction wattage	18.60 W
Nominal voltage	57 V
Nominal current	0.37 A

Photometrical data

Luminous flux	1100 lm
Luminous efficacy	61 lm/W
Luminous flux at 25 °C	1100 lm
Light color (designation)	LUMILUX DE LUXE Warm White
Color temperature	3000 K
Color rendering index Ra	≥90
Light color	930



Dimensions & Weight

Overall length	604.00 mm
Length	604.00 mm
Length with base excl. base pins/connection	590,00 mm
Width (incl. round luminaires)	26.00 mm
Height (incl. round luminaires)	26.00 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	86.00 g

Lifespan

Nominal lamp life time	20000 h
Service life	16000 h ¹⁾

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	19.00 kWh/1000h

Country-specific categorizations

ILCOS	FD-18/930-E-G13-26/600
Order reference	L 18W/930

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Chromaticity coordinate x	0,436
Chromaticity coordinate y	0,399
Beam angle	SPHERE_360
EPREL ID	546386
Model number	AC34161

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

DOWNLOAD DATA



Declarations of conformity
EC Declaration of Conformity - 2021 9C1-4077902-EN-00 - T8 DE LUXE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300011264	Sleeve 1	607 mm x 28 mm x 30 mm	90.00 g	0.51 dm ³
4050300236452	Shipping box 25	509 mm x 269 mm x 147 mm	2696.25 g	20.13 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.