

## PRODUCT DATASHEET

### L 40W/865 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



#### Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

#### Product benefits

- Excellent uniform illumination with no shadows

#### Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable



---

## TECHNICAL DATA

### Electrical data

Nominal wattage	40 W
Construction wattage	40.00 W
Nominal voltage	115 V

### Photometrical data

Luminous flux	2750 lm
Luminous efficacy	68 lm/W
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80...89
Light color	865

### Dimensions & Weight

Overall length	406.00 mm
Diameter	29.00 mm
Product weight	261.00 g

### Lifespan

Lifespan B50	13000 h
--------------	---------

### Additional product data

Base (standard designation)	G10q
Mercury content	3.6 mg

### Country-specific categorizations

Order reference	L 40W/865 C G10
-----------------	-----------------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
Length	406.00 mm
Height	29.00 mm
Width	29.00 mm

---

## EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gears

---

### Safety advice

- In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

---

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075719026	Sleeve 1	421 mm x 411 mm x 38 mm	451.00 g	6.58 dm <sup>3</sup>
4058075719033	Shipping box 12	452 mm x 436 mm x 431 mm	5865.00 g	84.94 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.