

## PRODUCT DATASHEET

### L SA 40 W/640

SA-Type T12 | Tubular fluorescent lamps 38 mm, for resonance double-choke circuits, with G13 base



#### Areas of application

- Street lighting
- Industry
- Outdoor applications only in suitable luminaires

#### Product benefits

- Stable and suitable for outdoor lighting or fixtures with little thermal insulation

#### Product features

- External ignition strip for improved ignition at low ambient temperatures
- Operation without starter




TECHNICAL DATA

Electrical data

Nominal wattage	40 W
Construction wattage	40.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	3000 lm
Luminous efficacy	75 lm/W
Luminous flux at 25 °C	3000 lm
Light color (designation)	Cold White
Color temperature	4000 K
Color rendering index Ra	≥60
Light color	640
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.75
Rated LLMF at 6,000 h	0.67
Rated LLMF at 8,000 h	0.60
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body
Rated lamp efficacy (standard co.)	75 lm/W



349629\_FL\_640

Dimensions & Weight

Overall length	1200.00 mm
Length with base excl. base pins/connection	1200 mm
Diameter	38 mm
Tube diameter	38 mm
Maximum diameter	38 mm

Product weight	275.00 g
----------------	----------

### Temperatures & operating conditions

Rated ambient temp.w.max.luminous	25.0 °C
-----------------------------------	---------

### Lifespan

Service life	4000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.67
Rated lamp survival factor at 8,000 h	0.60
Operation mode LLMF/LSF	50 Hz

### Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg
Design / version	SA-type
Product remark	Banned from 1.9.2021 following the Single Lighting Regulation

### Capabilities

Suitable for indoor	Yes
---------------------	-----

### Certificates & Standards

Energy efficiency class	G
Energy consumption	47.22 kWh/1000h

### Country-specific categorizations

ILCOS	FD-40/640-LC/-/P/-G13-38/1200
Order reference	L 40W/640 SA


### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1200.00 mm
Height	38 mm
Width	38 mm

### Safety advice

– In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

## DOWNLOAD DATA

Photometric and lighting design files		Document name
	Spectral power distribution	349629_FL_640

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300018331	Sleeve 1	1,216 mm x 40 mm x 43 mm	275.00 g	2.09 dm <sup>3</sup>
4050300207605	Shipping box 25	1,260 mm x 220 mm x 240 mm	7329.00 g	66.53 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.