

## PRODUCT DATASHEET

### SIG 1227

Low-voltage over-pressure lamps for 10 V systems, road traffic | Low-voltage over-pressure lamps for 10 V systems, road traffic



---

#### Areas of application

- Road traffic signalling systems

---

#### Product benefits

- Much higher luminous efficacy than high-voltage signal lamps
- Clearly improved lamp quality due to higher gas pressure and inert gas filling
- Leads to reduced power consumption of the signal installation
- High resistance against shock and vibration compared to high-voltage lamps
- Max. premature failure rate: 2 % up to 4,400 h (related to lamp failures only)
- Retrofit for 230 V systems (replace lamp and reflector and install transformer)

## TECHNICAL DATA

### Electrical data

Nominal wattage	20 W
Construction wattage	22.00 W
Nominal voltage	10 V

### Photometrical data

Luminous flux	270 lm
Luminous efficacy	13 lm/W
Color rendering index Ra	100
Light color	10

### Light technical data

Starting time	0 s
---------------	-----

### Dimensions & Weight

Overall length	67.00 mm
Light center length (LCL)	31,0 mm <sup>1)</sup>
Diameter	36,0 mm
Product weight	18.1 g

<sup>1)</sup> Distance from the coil to the lug of base

### Additional product data

Base (standard designation)	BA20s
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Bulb

### Capabilities

Burning position	s135
------------------	------

### Country-specific categorizations

Order reference	1227
-----------------	------


### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	BA20s
Length	67.00 mm
Height	36,0 mm
Width	36,0 mm

### Safety advice

- Use only in signal equipment/luminaires that are specially designed for the purpose. Protect the lamps against moisture during operation and installation.

### DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	GLS

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300831718	Unpacked 1		18.10 g	
4050300234991	Folding box 10	193 mm x 78 mm x 76 mm	213.00 g	1.14 dm <sup>3</sup>
4099854217739	Shipping box 200	410 mm x 400 mm x 179 mm	4620.00 g	29.36 dm <sup>3</sup>
4050300235004	Shipping box 100	407 mm x 175 mm x 203 mm	2002.00 g	14.46 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.