

PRODUCT DATASHEET SPC.T FR 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Domestic baking ovens

Product features

– Ambient temperature: up to 300 $^{\circ}\text{C}$




TECHNICAL DATA

Electrical data

| Nominal wattage | 15 W |
|----------------------|---------|
| Construction wattage | 15.00 W |
| Nominal voltage | 230 V |

Photometrical data

| Luminous flux | 85 lm |
|---|------------|
| Luminous efficacy | 5 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | > 99 |
| Light color | 927 |



349635_HAL_ohne_UVS

Light technical data

| Starting time | 0 s |
|---------------|-----|
|---------------|-----|

Dimensions & Weight

| Overall length | 57.00 mm |
|---|----------|
| Length with base excl. base pins/connection | 57.00 mm |
| Light center length (LCL) | 45,0 mm |
| Diameter | 26,0 mm |
| Product weight | 7.6 g |

Lifespan

Additional product data

| Base (standard designation) | E14 |
|-----------------------------|-----|
| Mercury-free | Yes |

Capabilities

Certificates & Standards

| Energy efficiency class | G |
|-------------------------|-----------------|
| Energy consumption | 15.00 kWh/1000h |

Country-specific categorizations

| ILCOS | IBT/F-15-230-E14-26 |
|-----------------|---------------------|
| Order reference | SPC.T26/57 FR 1 |

Energy labelling regulation data acc EU 2019/2015

| Non-directional or directional NDLS Mains or non-mains MLS Light source cap-type (or other electric interface) E14 Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 Model number AC35397,AC35397 | Lighting technology used | OTHER |
|--|---|-----------------|
| Light source cap-type (or other electric interface) Connected light source (CLS) No Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length Height 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence EPREL ID No | Non-directional or directional | NDLS |
| Connected light source (CLS) Color-tuneable light source No Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence EPREL ID No | Mains or non-mains | MLS |
| Color-tuneable light source Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence EPREL ID No | Light source cap-type (or other electric interface) | E14 |
| Envelope No High luminance light source No Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Connected light source (CLS) | No |
| High luminance light source Anti-glare shield No Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence EPREL ID No 114462 | Color-tuneable light source | No |
| Anti-glare shield Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360 T14462 | Envelope | No |
| Correlated colour temperature type SINGLE_VALUE Standby power 0.00 W Networked standby power for CLS 0 W Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360 EPREL ID SINGLE_VALUE SINGLE_VALUE SINGLE_VALUE SINGLE_VALUE SINGLE_VALUE 0.40 W 0.40 W 0.40 W 1.40 M 1.40 M | High luminance light source | No |
| Standby power0.00 WNetworked standby power for CLS0 WClaim of equivalent powerNoLength55.00 mmHeight26,0 mmWidth26,0 mmChromaticity coordinate x0.496Chromaticity coordinate y0.412Beam angle correspondenceSPHERE_360EPREL ID714462 | Anti-glare shield | No |
| Networked standby power for CLS Claim of equivalent power No Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y Beam angle correspondence SPHERE_360 EPREL ID 714462 | Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Standby power | 0.00 W |
| Length 55.00 mm Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Networked standby power for CLS | 0 W |
| Height 26,0 mm Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Claim of equivalent power | No |
| Width 26,0 mm Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Length | 55.00 mm |
| Chromaticity coordinate x 0.496 Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Height | 26,0 mm |
| Chromaticity coordinate y 0.412 Beam angle correspondence SPHERE_360 EPREL ID 714462 | Width | 26,0 mm |
| Beam angle correspondence SPHERE_360 EPREL ID 714462 | Chromaticity coordinate x | 0.496 |
| EPREL ID 714462 | Chromaticity coordinate y | 0.412 |
| | Beam angle correspondence | SPHERE_360 |
| Model number AC35397,AC35397 | EPREL ID | 714462 |
| | Model number | AC35397,AC35397 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

Spectral power distribution

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|---------------------------------------|------------------|--|
| PDF | Declarations of conformity | OVEN 15W 25W E14 | |
| | Photometric and lighting design files | Document name | |

349635_HAL_ohne_UVS

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300003085 | Folding box 1 | 27 mm x 27 mm x 61 mm | 9.60 g | 0.04 dm ³ |
| 4050300555171 | Bundle 10 | 135 mm x 54 mm x 61 mm | 96.00 g | 0.44 dm ³ |
| 4050300555188 | Shipping box 100 | 285 mm x 150 mm x 140 mm | 1010.00 g | 5.99 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.