

## PRODUCT DATASHEET

### SPC.T FR 25 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



#### Areas of application

- Domestic baking ovens

#### Product features

- Ambient temperature: up to 300 °C



TECHNICAL DATA

Electrical data

Nominal wattage	25 W
Construction wattage	25.00 W
Nominal voltage	230 V

Photometrical data

Luminous flux	140 lm
Luminous efficacy	5 lm/W
Lumen main.fact.at end of nom.life time	0.70
Color temperature	2700 K
Color rendering index Ra	> 99
Light color	927



349635\_HAL\_ohne\_UVS

Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight



Overall length	57.00 mm
Length with base excl. base pins/connection	57.00 mm
Light center length (LCL)	45,0 mm

Diameter	26,0 mm
Product weight	7.6 g

### Lifespan

Lifespan L70/B50 at 25 °C	1000 h
---------------------------	--------

### Additional product data

Base (standard designation)	E14
Mercury-free	Yes
Design / version	Frosted

### Capabilities

Dimmable	Yes
----------	-----

### Certificates & Standards

Energy efficiency class	G
Energy consumption	25.00 kWh/1000h

### Country-specific categorizations

ILCOS	IBT/F-25-230-E14-26
Order reference	SPC.T26/57 FR 2

### Energy labelling regulation data acc EU 2019/2015




Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.00 W
Networked standby power for CLS	0 W
Claim of equivalent power	No
Length	55.00 mm
Height	26,0 mm

Width	26,0 mm
Chromaticity coordinate x	0.487
Chromaticity coordinate y	0.416
Beam angle correspondence	SPHERE_360
EPREL ID	714464
Model number	AC35398,AC35398

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

### DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	SPC.T26 57 OVEN
	Declarations of conformity	OVEN 15W 25W E14
Photometric and lighting design files		Document name
	Spectral power distribution	349635_HAL_ohne_UVS

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300323596	Folding box 1	27 mm x 27 mm x 61 mm	9.60 g	0.04 dm <sup>3</sup>
4050300555195	Bundle 10	135 mm x 54 mm x 61 mm	96.00 g	0.44 dm <sup>3</sup>
4050300555201	Shipping box 100	285 mm x 150 mm x 140 mm	1010.00 g	5.99 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.