

# PRODUCT DATASHEET SPC.T CL 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



#### Areas of application

- Domestic baking ovens

#### Product features

- Ambient temperature: up to 300 °C




## TECHNICAL DATA

## Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	230 V
Nominal current	65 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	1.00

## Photometrical data

Luminous flux	60 lm
Luminous efficacy	4 lm/W
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027



349634\_HAL\_HV\_AK

# Light technical data

Starting time < 0.5 s
-----------------------

# Dimensions & Weight

Overall length	54.00 mm
Length with base excl. base pins/connection	55.00 mm
Diameter	17,0 mm
Product weight	5.9 g

# Temperatures & operating conditions

Ambient temperature renge	-20+300 °C
Ambient temperature range	-20+300 °C
Maximum temperature at tc test point	300 °C
Lifespan	
Lifespan L70/B50 at 25 °C	1000 h
Number of switching cycles	1000
Additional product data	
Base (standard designation)	E14
Mercury-free	Yes
Capabilities	
Dimmable	Yes
Certificates & Standards	
Energy efficiency class	G
Energy consumption	15.00 kWh/1000h
Type of protection	IP50
Photobiological safety group acc. to EN62778	RGO
Country-specific categorizations	
ILCOS	IBT/C-15-230-E14-17
Order reference	SPECIAL. CL 15W
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE

0 W
No
54.00 mm
17,0 mm
17,0 mm
0.4168
0.4970
SPHERE_360
714465

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	P Declarations of conformity OVEN 15W 25W E14	
	Photometric and lighting design files	Document name
	Spectral power distribution	349634_HAL_HV_AK

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300092928	Blister 1	140 mm x 120 mm x 18 mm	18.90 g	0.30 dm <sup>3</sup>
4050300066639	Folding box	19 mm x 19 mm x 62 mm	8.90 g	0.02 dm <sup>3</sup>
4050300093680	Shipping box 10	130 mm x 130 mm x 148 mm	264.00 g	2.50 dm <sup>3</sup>
4050300098500	Shipping box 50	204 mm x 110 mm x 78 mm	496.00 g	1.75 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.