

PRODUCT DATASHEET

SPC.T OVEN CL 15 W 230 V E14

SPECIAL OVEN T | Incandescent lamps, tubular shape, for oven lighting



Areas of application

- Domestic baking ovens

Product features

- Ambient temperature: up to 300 °C




TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	230 V

Photometrical data

Luminous flux	85 lm
Luminous efficacy	5 lm/W
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027



349635_HAL_ohne_UVS

Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight

Overall length	50.00 mm
Length with base excl. base pins/connection	50.00 mm
Light center length (LCL)	43,0 mm
Diameter	22,0 mm
Product weight	10.00 g

Lifespan

Lifespan L70/B50 at 25 °C	1000 h
---------------------------	--------

Additional product data

Base (standard designation)	E14
Mercury-free	Yes
Design / version	Clear

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	15.00 kWh/1000h

Country-specific categorizations

ILCOS	IBT/C-15-230-E14-22
Order reference	SPC.T OVEN CL 1



Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.00 W
Networked standby power for CLS	0 W
Claim of equivalent power	No
Length	50.00 mm
Height	22,0 mm
Width	22,0 mm
Chromaticity coordinate x	0.493
Chromaticity coordinate y	0.412
Beam angle correspondence	SPHERE_360
EPREL ID	714477
Model number	AC35392,AC35392

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	SPC.T OVEN 15W SPC.T25 57 10W
Photometric and lighting design files		Document name
	Spectral power distribution	349635_HAL_ohne_UVS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300003108	Folding box 1	29 mm x 28 mm x 68 mm	14.00 g	0.06 dm ³
4050300554495	Bundle 10	58 mm x 140 mm x 68 mm	140.00 g	0.55 dm ³
4050300554501	Shipping box 100	308 mm x 156 mm x 149 mm	1510.00 g	7.16 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.