

# PRODUCT DATASHEET OT FIT 35/220...240/700 CS L G2

OPTOTRONIC® FIT CS L G2 | Linear / Area Constant Current - Non dimmable



#### Areas of application

- Linear lighting for office, education, industry, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I

## Product benefits

- Flexible current setting (DIPswitch 4 currents)
- Lifetime: up to 100,000 h (temperature at T  $_{\rm C}$  = 65 °C, max. 10 % failure rate)
- High efficiency
- High quality of light thanks to low output ripple current
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

#### **Product features**

- Line frequency: 0 Hz  $\mid$  50 Hz  $\mid$  60 Hz
- Versatile scope of application due to output power range of up to 75 W
- Supply voltage: 220...240 V
- Available with output current range: up to 1,400 mA
- SELV system

# TECHNICAL DATA

# Electrical data

Nominal wattage	45.00 W	
Nominal output power	13.535.7 W	
Nominal voltage	220240 V	
Nominal output voltage	2751 V	
Input voltage AC	198264 V <sup>1)</sup>	
Input voltage DC	176276 V	
U-OUT (working voltage)	< 60 V	
Nominal output current	500 mA / 600 mA / 650 mA / 700 mA	
Inrush current	16 A	
Output current tolerance	±7,5 %	
Output ripple current (100 Hz)	< 5 %	
Mains frequency	0/50/60 Hz	
Total harmonic distortion	< 10 %	
Power factor $\lambda$	0.98	
ECG efficiency	≤86 %	
Device power loss	5.8 W	
Max. ECG no. on circuit breaker 10 A (B)	21	
Max. ECG no. on circuit breaker 16 A (B)	34	
Max. ECG no. on circuit breaker 25 A (B)	-	
Surge capability (L/N-Ground)	2 kV	
Surge capability (L-N)	1 kV	
Galvanic isolation	SELV	
Flickering metric (Pst LM)	≤1	

<sup>1)</sup> Permitted voltage range

# Photometrical data

Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

# Dimensions & Weight



Length	280.00 mm
Mounting hole spacing, length	270,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup>
Cable cross-section, output side	0.51.5 mm <sup>2</sup>
Wire preparation length, input side	8.59.5 mm
Wire preparation length, output side	8.59.5 mm
Product weight	205.00 g

### Colors & materials

Casing material	Metal
Body material	Metal

# Temperatures & operating conditions

Ambient temperature range	-25+50 °C
Maximum temperature at tc test point	80 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

# Lifespan

ECG lifetime	50000 h / 100000 h <sup>1)</sup>
--------------	----------------------------------

<sup>1)</sup> At maximum T  $_{\rm C}$  = 75°C / 10% failure rate / At T  $_{\rm C}$  = 65 °C / 10 % failure rate

# Additional product data

Encapsulated
--------------

# Capabilities

Dimmable	No
Overheating protection	Automatic reversible
Overload protection	Non-reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	1
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

## Certificates & Standards

Approval marks – approval	CE / EL / ENEC 10 / VDE-EMC / CCC / RCM
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 62384 / Acc. to EN 61000-3-2 / Acc. to EN 61000-3-3 / Acc. to EN 61547
Protection class	1
Type of protection	IP20

## LOGISTICAL DATA

Temperature range at storage -2585 °C
---------------------------------------

## DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	OT FIT 35 55 75 220-240 D LT2 L	
POF	Declarations of conformity	INOTEC- Conformity declaration AM04351_OT_FIT_35_220-240_700_CS_L_EL	
POF	Declarations of conformity	EU Declaration of Conformity 3666934	
POF	Declarations of conformity	711957_Declaration of Conformity OT FIT CS L	
PDF	Certificates	VDE ENEC Certificate 40046756	
PDF	Certificates	VDE EMC Certificate 40046714	
PDF	Certificates	VDE EMC Certificate 40038482	
POF	Certificates	INOTEC Certificate OT FIT 35/700 CS L G2 appendix	
POF	Certificates	INOTEC Certificate OT FIT 35/700 CS L G2	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899522534	Unpacked 1		215.00 g	
4052899522541	Shipping box 20	303 mm x 159 mm x 101 mm	4419.00 g	4.87 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.