

# PRODUCT DATASHEET OTi DALI 15/220...240/1A0 LT2

OPTOTRONIC® Intelligent – DALI LT2 | Compact constant current LED drivers



#### Areas of application

- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for use in luminaires with flexible current setting (DALI, CLO, LEDset)
- Suitable for indoor SELV installations
- Suitable for luminaires of protection classes I and II
- Suitable for downlights, spotlights and LED panels
- Installation via Cable Clamp Kit possible (depending on version of product)

#### **Product benefits**

- Versatile DALI window driver due to flexible output characteristic
- Very high efficiency
- Protection of the system thanks to thermal management and Smart Control
- High-quality dimming of 1...100 % by amplitude dimming

#### Versatile scope of application due to OSRAM DALI Technology:

- Easy to use in corridors and restrooms because of three-level Corridor function
- Touch DIM application: easy to control via pushbutton or sensor
- Energy efficient Touch DIM operation due to automatic switch-off at sufficient residual light
- Suitable for emergency Installations (acc. to EN 60598-2-22 and IEC 61347-2-13, appendix J) thanks to DC detection (0 Hz, pulsating DC), on/off switchable
- Feedback of power consumption and operating hours (Fit for SMART GRID)
- Suitable for buildings according to EPBD/BREEAM/LEED due to automatic Constant Lumen Output setting

#### Product features

- Supply voltage: 220...240 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Line voltage: 198...264 V
- Safety according to EN 61347-1, 61347-2-3, 61347-2-13, 62384
- RI suppression: to EN 55015/CISPR 15
- Line harmonics according to EN 61000-3-2

- Immunity according to EN 61547
- Lifetime: up to 100,000 h
- Type of protection: IP20
- Independent connection via through-looping (except OTi DALI 15)

## **TECHNICAL DATA**

# Electrical data

Nominal wattage	18.00 W
Nominal output power	18 W <sup>1)</sup>
Nominal voltage	220240 V
Nominal output voltage	7,554 V <sup>2)</sup>
Input voltage AC	198264 V <sup>3)</sup>
Input voltage DC	176276 V
U-OUT (working voltage)	60 V
Nominal current	0.12 A
Nominal output current	1501050 mA <sup>4)</sup>
Inrush current	5 A
Output current tolerance	±3 %
Output ripple current (100 Hz)	< 2 % <sup>5)</sup>
Mains frequency	50/60 Hz
Total harmonic distortion	< 10 % <sup>6)</sup>
Power factor λ	0.95
ECG efficiency	88 % 7)
Device power loss	2,4 W
Max. ECG no. on circuit breaker 10 A (B)	82
Max. ECG no. on circuit breaker 16 A (B)	130
Max. ECG no. on circuit breaker 25 A (B)	
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Power loss in stand-by mode	≤0,27 W

<sup>1)</sup> Partial load 3...18 W

# Dimensions & Weight

<sup>2) &</sup>lt;sub>Maximum 60 V</sub>


<sup>3)</sup> Permitted voltage range

<sup>4) ±5%</sup> 

<sup>5)</sup> Ripple average at 100 Hz %

<sup>6)</sup> At full load, 220...240 V, 50 Hz / see graphs

<sup>7)</sup> Typical / At full load and 230 V



Length	95.00 mm
Width	53.00 mm
Height	30.00 mm
Cable cross-section, input side	0.21.5 mm <sup>2</sup> 1)
Cable cross-section, output side	0.21.5 mm <sup>2</sup> 1)
Wire preparation length, input side	8.09.0 mm
Wire preparation length, output side	8.09.0 mm
Product weight	100.00 g

<sup>1)</sup> Solid or flexible leads

## Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

## Temperatures & operating conditions

Ambient temperature range	-20+50 °C
Maximum temperature at tc test point	75 °C <sup>1)</sup>
Max.housing temperature in case of fault	100 °C
Permitted rel. humidity during operation	585 % <sup>2)</sup>

<sup>1)</sup> Maximum at the Tc-point

## Lifespan

ECG lifetime	50000 h / 100000 h <sup>1)</sup>

<sup>1)</sup>  $T_c$  = 75°C, 0.2% / 1,000 h failure rate /  $T_c$  = 65°C, 0.1% / 1,000 h failure rate

# Additional product data

Encapsulated	No

<sup>2)</sup> Maximum 56 days/year at 85 %

# Capabilities

Dimmable	Yes
Dimming interface	DALI / Touch DIM / Touch DIM Sensor
Dimming range	1100 % 1)
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	1711
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

<sup>1)</sup> For maximum nominal output current

## Certificates & Standards

Approval marks – approval	ENEC 10 / VDE / EMC / EL / CE
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384
Protection class	П
Type of protection	IP20

## LOGISTICAL DATA

Temperature range at storage	-2585 °C

# Accessories Optional

Product image	Product name	EAN
	OT CABLE CLAMP F-STYLE	4052899325555
	OT CABLE CLAMP F-STYLE	4052899325555

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
POF	User instruction / safety instructions	OPTOTRONIC LED Power Supply
POF	Declarations of conformity	EU Declaration of Conformity 3365628
POF	Certificates	OTI DALI 15 LT2 INOTEC AM34566 210720

	Documents and certificates	Document name
POF	Certificates	730563_VDE Certificate
POF	Certificates	664763_CB-Certificate-OTi DALI 15
POF	Certificates	OTI DALI 15 LT2 EATON AM34566 210720
PDF	Certificates	INOTEC-Conformity declaration AB32361 OTi DALI 15/220-240/1A0 LT2
PDF	Certificates	EATON(CEAG)-Conformity declaration AB32361 OTi DALI 15/220-240/1A0 LT2
POF	Certificates	VDE ENEC Certificate 40038447
	CAD/BIM files	Document name
POF	CAD data 3D PDF	673589_OT Cable Clamp F Style CADPDF 61119

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899324879	Unpacked 1		100.00 g	
4052899324886	Shipping box 20	284 mm x 207 mm x 90 mm	2270.00 g	5.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.