

PRODUCT DATASHEET

OTi DALI 160/220-240/ 24 2CH DT6/8 G3

CV Power supplies with DALI | CV Power supplies with DALI



Areas of application

- Cove lighting, wall washer, corridor, handrail, luminous ceilings
- Suitable for use in luminaires of protection class I and II

Product benefits

- Intelligent power matching thanks to Smart power supply
- Slim form factor for mounting on the cove or in linear luminaires
- No stroboscopic effect thanks to patented high PWM frequency management (> 2 kHz)
- Suitable for installation in emergency lighting systems according to EN 60598-2-22
- Available as single-channel or multi-channel with DT6 and DT8 in one device
- DALI message detection "LED Module failure"
- IP rating: IP20

Product features

- Dimmable via Touch DIM
- LED driver whose output power can be shared arbitrarily among the 2 or 4 channels
- Dimming range: 0.1...100 %
- Line frequency: 0 Hz | 50 Hz | 60 Hz

TECHNICAL DATA

Electrical data

Nominal wattage	160.00 W
Nominal output power	160 W
Nominal voltage	220...240 V
Nominal output voltage	24 V ¹⁾
Input voltage range	220...240 V
Input voltage AC	198...264 V
U-OUT (working voltage)	24.2 V
Inrush current	57 A
Mains frequency	50/60 Hz
Total harmonic distortion	< 5 %
Power factor λ	> 0.95
ECG efficiency	93 % ²⁾
Device power loss	11 W
Max. ECG no. on circuit breaker 10 A (B)	8
Max. ECG no. on circuit breaker 16 A (B)	13
Max. ECG no. on circuit breaker 25 A (B)	12
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Flickering metric (Pst LM)	≤ 1

¹⁾ DC voltage

²⁾ at 230 V, 50 Hz

Photometrical data

Flickering metric (Pst LM)	≤ 1
Stroboscope effect metric (SVM)	≤ 0.4

Dimensions & Weight

Length	300.0 mm
Mounting hole spacing, length	258 mm
Width	50.00 mm
Height	35.00 mm
Cable cross-section, input side	0,5...2,5 mm ²
Cable cross-section, output side	0,5...2,5 mm ²
Wire preparation length, input side	6,0 mm
Wire preparation length, output side	6,0 mm

Product weight	380.00 g
----------------	----------

Colors & materials

Casing material	Plastic
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h
--------------	---------

Capabilities

Dimmable	Yes
Dimming interface	DALI-2 / Corridor / Touch DIM
Dimming range	0...100 %
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Suitable for fixtures with prot. class	I,II
Type of connection, output side	Screw terminal

Certificates & Standards

Approval marks – approval	BIS / CCC / EAC / EL / ENEC 10 / RCM / VDE / VDE-EMC
Standards	Acc. to EN 55015 / Acc. to EN 60598-2-22 / Acc. to EN 61000-3-2 / Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 61547 / Acc. to EN 62384 / Acc. to EN 62386
Protection class	II
Type of protection	IP20






LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

EQUIPMENT / ACCESSORIES

– Suitable for 24 V LED modules

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	OTI DALI 160
	Declarations of conformity	OTI DALI 50 80 160 -220-240-24 4CHDT6-8
	Declarations of conformity UKCA	OTI DALI 50 80 160 -220-240-24 4CHDT6-8
	Certificates	VDE Certificate
	EU Data Act	Connected Products and Related Software and Services

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172274326	Unpacked 1	360 mm x 30 mm x 21 mm		0.23 dm ³
4062172274333	Shipping box 20	335 mm x 268 mm x 167 mm	8065.00 g	14.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.