

# PRODUCT DATASHEET OT SLIM 100/220-240/24

CV Power supplies 24 V | CV Power supplies 24 V



## Areas of application

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

## Product benefits

- Installation in cold and hot environments
- Very stable output power
- High electronical reversible short-circuit, overload, overtemperature protection
- Independent installation possible

## **Product features**

- Type of protection: IP20
- Wide operating temperature range: -20...+50 °C
- Lifetime: up to 50,000 h (temperature at max.  $t_c$ )

# TECHNICAL DATA

# Electrical data

Nominal wattage	110.00 W
Nominal output power	100 W
Nominal voltage	220240 V
Nominal output voltage	24.2 V
Input voltage AC	195.5276 V
Input voltage DC	176250 V
U-OUT (working voltage)	24 V
Inrush current	50 A
Mains frequency	50/60 Hz
Total harmonic distortion	< 5 %
Power factor $\lambda$	0.95
Device power loss	9.9 W
Max. ECG no. on circuit breaker 10 A (B)	6
Max. ECG no. on circuit breaker 16 A (B)	10
Max. ECG no. on circuit breaker 25 A (B)	10
Surge capability (L-N)	1 kV
Galvanic isolation	SELV

# Dimensions & Weight



Length	374.00 mm
Mounting hole spacing, length	326.0 mm
Width	30.00 mm
Height	18.50 mm
Cable cross-section, input side	0.751.5 mm <sup>2</sup>
Cable cross-section, output side	0.751.5 mm <sup>2</sup>
Wire preparation length, input side	5,0 mm
Wire preparation length, output side	5,0 mm
Product weight	220.00 g

## Colors & materials

Casing material	Plastic
-----------------	---------

Body material	Plastic		
Temperatures & operating conditions			
Ambient temperature range	-25+45 °C		
Maximum temperature at tc test point	80 °C		
Max.housing temperature in case of fault	110 °C		
Permitted rel. humidity during operation	585 % <sup>1)</sup>		

<sup>1)</sup> Maximum 56 days/year at 85 %

## Lifespan

ECG lifetime	50000 h

## Capabilities

Dimmable	No
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Suitable for fixtures with prot. class	1/11
Type of connection, output side	Screw terminal

## Certificates & Standards

Approval marks – approval	CE / CB / ENEC / CCC / EAC / RCM / BIS	
Standards	Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to EN 55015 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3	
Protection class	П	
Type of protection	IP20	

# LOGISTICAL DATA

Temperature range at storage	-40+85 °C
------------------------------	-----------

## ADDITIONAL PRODUCT INFORMATION

- EMI pass verified with wire length of 2 m, from the ECG to the LED module at full load.
- Wiring longer than 2 m from ECG to LED module is possible, but site installation conditions may interfere with EMI with these longer cables. EMI is therefore not verified in this condition.
- For wires longer than 2 m, the appropriate cable cross section must be carefully selected to reduce voltage drop.

## **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	14614288 OT SLIM

CAD/BIM files	Document name
CAD STEP 3D	OT SLIM 100-220-240-24

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172135870	Unpacked 1			
4062172135887	Shipping box 30	387 mm x 192 mm x 150 mm	7058.00 g	11.15 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.