

PRODUCT DATASHEET OT Programmer

OT Programmer | USB Programming interface



Product features

- Standard USB interface
- Very fast programming of single OPTOTRONIC devices with the Prog +/- interface
- Programming without applying mains voltage to the driver
- Suitable only for non-DALI OPTOTRONIC devices with the Prog +/- interface

TECHNICAL DATA

Electrical data

Nominal voltage	5 V ¹⁾
Mains frequency	0 Hz

¹⁾ Supplied by USB

Dimensions & Weight

Length	120.0 mm
Width	76.00 mm
Height	28.00 mm
Product weight	200.00 g

Colors & materials

Temperatures & operating conditions

Ambient temperature range	0+50 °C

Capabilities

Dimmable	No

Certificates & Standards

Protection class	1
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage -2580 °C	
---------------------------------------	--

EQUIPMENT / ACCESSORIES

- Programmable via Tuner4TRONIC software

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	643182_EC Conformity OT Programmer
PDF	Declarations of conformity	642506_OT Programmer EC-Declaration of Conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899209640	Unpacked 1			
4052899209657	Shipping box	210 mm x 133 mm x 89 mm	289.00 g	2.49 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.